



ANDROID STATIC ANALYSIS REPORT



 MapSpoto (1.4.0)

File Name:


universal.apk

Package Name: com.voivoo.mapspoto

Scan Date: June 5, 2026, 5:34 a.m.






App Security Score: **54/100 (MEDIUM RISK)**

Grade:



Trackers Detection: **1/432**

FINDINGS SEVERITY

 HIGH	 MEDIUM	 INFO	 SECURE	 HOTSPOT
1	16	3	2	2

FILE INFORMATION

File Name: universal.apk

Size: 89.69MB

MD5: e0c1e186121af870c1579c8bc3d27023

SHA1: 1118b6af366cca4461ea7f58cf4738a3292a55aa

SHA256: 8b8bb70bd0ee006daa2f725ded428d6f5e2d957ac90898631bdf1ef5ef7c24e4

APP INFORMATION

App Name: MapSpoto

Package Name: com.voivoo.mapspoto

Main Activity: com.voivoo.mapspoto.MainActivity

Target SDK: 36

Min SDK: 29

Max SDK:

Android Version Name: 1.4.0

Android Version Code: 45

APP COMPONENTS

Activities: 5

Services: 10
Receivers: 12
Providers: 10
Exported Activities: 0
Exported Services: 1
Exported Receivers: 3
Exported Providers: 1

CERTIFICATE INFORMATION

Binary is signed
v1 signature: False
v2 signature: False
v3 signature: True
v4 signature: False
X.509 Subject: C=DE, ST=Niedersachsen, L=Burgdorf, O=Liming Wang, OU=Liming Wang, CN=Liming Wang
Signature Algorithm: rsassa_pkcs1v15
Valid From: 2026-05-02 19:37:59+00:00
Valid To: 2053-09-17 19:37:59+00:00
Issuer: C=DE, ST=Niedersachsen, L=Burgdorf, O=Liming Wang, OU=Liming Wang, CN=Liming Wang
Serial Number: 0x2a0b58a79bda9787
Hash Algorithm: sha256
md5: 6ad84bdf5c558b8b010950808a046d3a
sha1: 611afa41d23d9ec635705ea90cff0bbbb65289d7
sha256: 67ea75c237710dbd66f7d8afd4a318a02ee47eb23acc1e60d5189a153fa155dd
sha512: 00a00f494ab2f542d76abc687679f27490c67ad126899ba6e88e430b2575c650e206b0b9c7d43fb8a3fcdad33a4424f60076d94ca61cc5ce7cecd57fa2799130
PublicKey Algorithm: rsa
Bit Size: 2048
Fingerprint: d87d9134324601e755893ad1c5bf8f1986ccbe4c09e96320136b53e31610544c
Found 1 unique certificates

APPLICATION PERMISSIONS

PERMISSION	STATUS	INFO	DESCRIPTION
------------	--------	------	-------------

PERMISSION	STATUS	INFO	DESCRIPTION
android.permission.ACCESS_COARSE_LOCATION	dangerous	coarse (network-based) location	Access coarse location sources, such as the mobile network database, to determine an approximate phone location, where available. Malicious applications can use this to determine approximately where you are.
android.permission.ACCESS_FINE_LOCATION	dangerous	fine (GPS) location	Access fine location sources, such as the Global Positioning System on the phone, where available. Malicious applications can use this to determine where you are and may consume additional battery power.
android.permission.INTERNET	normal	full Internet access	Allows an application to create network sockets.
android.permission.MODIFY_AUDIO_SETTINGS	normal	change your audio settings	Allows application to modify global audio settings, such as volume and routing.
android.permission.READ_MEDIA_AUDIO	dangerous	allows reading audio files from external storage.	Allows an application to read audio files from external storage.
android.permission.READ_MEDIA_IMAGES	dangerous	allows reading image files from external storage.	Allows an application to read image files from external storage.

PERMISSION	STATUS	INFO	DESCRIPTION
android.permission.READ_MEDIA_VIDEO	dangerous	allows reading video files from external storage.	Allows an application to read video files from external storage.
android.permission.READ_MEDIA_VISUAL_USER_SELECTED	dangerous	allows reading user-selected image or video files from external storage.	Allows an application to read image or video files from external storage that a user has selected via the permission prompt photo picker. Apps can check this permission to verify that a user has decided to use the photo picker, instead of granting access to READ_MEDIA_IMAGES or READ_MEDIA_VIDEO . It does not prevent apps from accessing the standard photo picker manually. This permission should be requested alongside READ_MEDIA_IMAGES and/or READ_MEDIA_VIDEO , depending on which type of media is desired.
android.permission.RECORD_AUDIO	dangerous	record audio	Allows application to access the audio record path.
android.permission.VIBRATE	normal	control vibrator	Allows the application to control the vibrator.
android.permission.ACCESS_NETWORK_STATE	normal	view network status	Allows an application to view the status of all networks.
android.permission.POST_NOTIFICATIONS	dangerous	allows an app to post notifications.	Allows an app to post notifications
android.permission.WAKE_LOCK	normal	prevent phone from sleeping	Allows an application to prevent the phone from going to sleep.

PERMISSION	STATUS	INFO	DESCRIPTION
com.google.android.c2dm.permission.RECEIVE	normal	recieve push notifications	Allows an application to receive push notifications from cloud.
android.permission.CAMERA	dangerous	take pictures and videos	Allows application to take pictures and videos with the camera. This allows the application to collect images that the camera is seeing at any time.
android.permission.USE_BIOMETRIC	normal	allows use of device-supported biometric modalities.	Allows an app to use device supported biometric modalities.
android.permission.USE_FINGERPRINT	normal	allow use of fingerprint	This constant was deprecated in API level 28. Applications should request USE_BIOMETRIC instead.
com.voivoo.mapspoto.DYNAMIC_RECEIVER_NOT_EXPORTED_PERMISSION	unknown	Unknown permission	Unknown permission from android reference
com.google.android.finsky.permission.BIND_GET_INSTALL_REFERRER_SERVICE	normal	permission defined by google	A custom permission defined by Google.
com.sec.android.provider.badge.permission.READ	normal	show notification count on app	Show notification count or badge on application launch icon for samsung phones.
com.sec.android.provider.badge.permission.WRITE	normal	show notification count on app	Show notification count or badge on application launch icon for samsung phones.

PERMISSION	STATUS	INFO	DESCRIPTION
com.htc.launcher.permission.READ_SETTINGS	normal	show notification count on app	Show notification count or badge on application launch icon for htc phones.
com.htc.launcher.permission.UPDATE_SHORTCUT	normal	show notification count on app	Show notification count or badge on application launch icon for htc phones.
com.sonyericsson.home.permission.BROADCAST_BADGE	normal	show notification count on app	Show notification count or badge on application launch icon for sony phones.
com.sonymobile.home.permission.PROVIDER_INSERT_BADGE	normal	show notification count on app	Show notification count or badge on application launch icon for sony phones.
com.anddoes.launcher.permission.UPDATE_COUNT	normal	show notification count on app	Show notification count or badge on application launch icon for apex.
com.majeur.launcher.permission.UPDATE_BADGE	normal	show notification count on app	Show notification count or badge on application launch icon for solid.
com.huawei.android.launcher.permission.CHANGE_BADGE	normal	show notification count on app	Show notification count or badge on application launch icon for huawei phones.

PERMISSION	STATUS	INFO	DESCRIPTION
com.huawei.android.launcher.permission.READ_SETTINGS	normal	show notification count on app	Show notification count or badge on application launch icon for huawei phones.
com.huawei.android.launcher.permission.WRITE_SETTINGS	normal	show notification count on app	Show notification count or badge on application launch icon for huawei phones.
android.permission.READ_APP_BADGE	normal	show app notification	Allows an application to show app icon badges.
com.oppo.launcher.permission.READ_SETTINGS	normal	show notification count on app	Show notification count or badge on application launch icon for oppo phones.
com.oppo.launcher.permission.WRITE_SETTINGS	normal	show notification count on app	Show notification count or badge on application launch icon for oppo phones.
me.everything.badger.permission.BADGE_COUNT_READ	unknown	Unknown permission	Unknown permission from android reference
me.everything.badger.permission.BADGE_COUNT_WRITE	unknown	Unknown permission	Unknown permission from android reference

FILE	DETAILS	
classes.dex	FINDINGS	DETAILS
	yara_issue	yara issue - dex file recognized by apkid but not yara module
	Anti-VM Code	Build.FINGERPRINT check Build.MANUFACTURER check
	Compiler	unknown (please file detection issue!)
classes2.dex	FINDINGS	DETAILS
	yara_issue	yara issue - dex file recognized by apkid but not yara module
	Anti-VM Code	Build.FINGERPRINT check Build.MANUFACTURER check possible Build.SERIAL check
	Compiler	unknown (please file detection issue!)

FILE	DETAILS	
classes3.dex	FINDINGS	DETAILS
	yara_issue	yara issue - dex file recognized by apkid but not yara module
	Anti-VM Code	Build.FINGERPRINT check Build.MODEL check Build.MANUFACTURER check Build.PRODUCT check Build.HARDWARE check Build.BOARD check Build.TAGS check possible VM check
	Anti Debug Code	Debug.isDebuggerConnected() check
	Compiler	unknown (please file detection issue!)
classes4.dex	FINDINGS	DETAILS
	yara_issue	yara issue - dex file recognized by apkid but not yara module
	Anti-VM Code	Build.MANUFACTURER check
	Compiler	unknown (please file detection issue!)

FILE	DETAILS	
classes5.dex	FINDINGS	DETAILS
	yara_issue	yara issue - dex file recognized by apkid but not yara module
	Compiler	unknown (please file detection issue!)

BROWSABLE ACTIVITIES

ACTIVITY	INTENT
com.voivoo.mapspoto.MainActivity	Schemes: mapspoto://, com.voivoo.mapspoto://, Path Prefixes: /oauthredirect,

NETWORK SECURITY

NO	SCOPE	SEVERITY	DESCRIPTION
----	-------	----------	-------------

CERTIFICATE ANALYSIS

HIGH: 0 | WARNING: 0 | INFO: 1

TITLE	SEVERITY	DESCRIPTION
-------	----------	-------------

TITLE	SEVERITY	DESCRIPTION
Signed Application	info	Application is signed with a code signing certificate

Q MANIFEST ANALYSIS

HIGH: 0 | WARNING: 5 | INFO: 0 | SUPPRESSED: 0

NO	ISSUE	SEVERITY	DESCRIPTION
1	Content Provider (expo.modules.clipboard.ClipboardFileProvider) is not Protected. [android:exported=true]	warning	A Content Provider is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
2	Broadcast Receiver (com.google.firebase.iid.FirebaseInstanceIdReceiver) is Protected by a permission, but the protection level of the permission should be checked. Permission: com.google.android.c2dm.permission.SEND [android:exported=true]	warning	A Broadcast Receiver is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device. It is protected by a permission which is not defined in the analysed application. As a result, the protection level of the permission should be checked where it is defined. If it is set to normal or dangerous, a malicious application can request and obtain the permission and interact with the component. If it is set to signature, only applications signed with the same certificate can obtain the permission.
3	Service (androidx.work.impl.background.systemjob.SystemJobService) is Protected by a permission, but the protection level of the permission should be checked. Permission: android.permission.BIND_JOB_SERVICE [android:exported=true]	warning	A Service is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device. It is protected by a permission which is not defined in the analysed application. As a result, the protection level of the permission should be checked where it is defined. If it is set to normal or dangerous, a malicious application can request and obtain the permission and interact with the component. If it is set to signature, only applications signed with the same certificate can obtain the permission.

NO	ISSUE	SEVERITY	DESCRIPTION
4	Broadcast Receiver (androidx.work.impl.diagnostics.DiagnosticsReceiver) is Protected by a permission, but the protection level of the permission should be checked. Permission: android.permission.DUMP [android:exported=true]	warning	A Broadcast Receiver is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device. It is protected by a permission which is not defined in the analysed application. As a result, the protection level of the permission should be checked where it is defined. If it is set to normal or dangerous, a malicious application can request and obtain the permission and interact with the component. If it is set to signature, only applications signed with the same certificate can obtain the permission.
5	Broadcast Receiver (androidx.profileinstaller.ProfileInstallReceiver) is Protected by a permission, but the protection level of the permission should be checked. Permission: android.permission.DUMP [android:exported=true]	warning	A Broadcast Receiver is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device. It is protected by a permission which is not defined in the analysed application. As a result, the protection level of the permission should be checked where it is defined. If it is set to normal or dangerous, a malicious application can request and obtain the permission and interact with the component. If it is set to signature, only applications signed with the same certificate can obtain the permission.

</> CODE ANALYSIS

HIGH: 1 | WARNING: 9 | INFO: 3 | SECURE: 1 | SUPPRESSED: 0

NO	ISSUE	SEVERITY	STANDARDS	FILES
				com/bumptech/glide/GeneratedAppGlideModuleImpl.java com/bumptech/glide/Glide.java com/bumptech/glide/disklruCache/DiskLruCache.java com/bumptech/glide/gifdecoder/GifHeaderParser.java com/bumptech/glide/gifdecoder/StandardGifDecoder.java com/bumptech/glide/integration/avif/AvifByteBufferBitmapDecoder.java com/bumptech/glide/load/data/AssetPathFetcher.java com/bumptech/glide/load/data/HttpUrlFetcher.java

NO	ISSUE	SEVERITY	STANDARDS	<p>com/bumptechn/glide/load/data/LocalUriFetcher.java com/bumptechn/glide/load/data/mediastore/Thumb Fetcher.java</p> <p>FILES</p> <p>com/bumptechn/glide/load/data/mediastore/Thumb nailStreamOpener.java com/bumptechn/glide/load/engine/DecodeJob.java com/bumptechn/glide/load/engine/DecodePath.java com/bumptechn/glide/load/engine/Engine.java com/bumptechn/glide/load/engine/GlideException.ja va com/bumptechn/glide/load/engine/SourceGenerator. java com/bumptechn/glide/load/engine/bitmap_recycle/Lr uArrayPool.java com/bumptechn/glide/load/engine/bitmap_recycle/Lr uBitmapPool.java com/bumptechn/glide/load/engine/cache/DiskLruCac heWrapper.java com/bumptechn/glide/load/engine/cache/MemorySiz eCalculator.java com/bumptechn/glide/load/engine/executor/GlideEx ecutor.java com/bumptechn/glide/load/engine/executor/Runtime Compat.java com/bumptechn/glide/load/engine/prefill/BitmapPre FillRunner.java com/bumptechn/glide/load/model/ByteBufferEncode r.java com/bumptechn/glide/load/model/ByteBufferFileLoa der.java com/bumptechn/glide/load/model/FileLoader.java com/bumptechn/glide/load/model/ResourceLoader.j ava com/bumptechn/glide/load/model/ResourceUriLoade r.java com/bumptechn/glide/load/model/StreamEncoder.ja va com/bumptechn/glide/load/resource/DefaultOnHead erDecodedListener.java com/bumptechn/glide/load/resource/bitmap/Bitmap Encoder.java com/bumptechn/glide/load/resource/bitmap/BitmapI mageDecoderResourceDecoder.java com/bumptechn/glide/load/resource/bitmap/DefaultI</p>

NO	ISSUE	SEVERITY	STANDARDS	<p>mageHeaderParser.java Files com/bumptech/glide/load/resource/bitmap/Downsampler.java</p>
				<p>com/bumptech/glide/load/resource/bitmap/DrawableToBitmapConverter.java com/bumptech/glide/load/resource/bitmap/HardwareConfigState.java com/bumptech/glide/load/resource/bitmap/TransformationUtils.java com/bumptech/glide/load/resource/bitmap/VideoDecoder.java com/bumptech/glide/load/resource/gif/ByteBufferGifDecoder.java com/bumptech/glide/load/resource/gif/GifDrawableEncoder.java com/bumptech/glide/load/resource/gif/StreamGifDecoder.java com/bumptech/glide/manager/DefaultConnectivityMonitorFactory.java com/bumptech/glide/manager/RequestTracker.java com/bumptech/glide/manager/SingletonConnectivityReceiver.java com/bumptech/glide/module/ManifestParser.java com/bumptech/glide/request/SingleRequest.java com/bumptech/glide/request/target/CustomViewTarget.java com/bumptech/glide/request/target/ViewTarget.java com/bumptech/glide/signature/ApplicationVersionSignature.java com/bumptech/glide/util/ContentLengthInputStream.java com/bumptech/glide/util/pool/FactoryPools.java com/canhub/cropper/BitmapUtils.java com/canhub/cropper/CropImageActivity.java com/canhub/cropper/utills/GetUriForFileKt.java com/caverock/androidsvg/CSSParser.java com/caverock/androidsvg/SVG.java com/caverock/androidsvg/SVGAndroidRenderer.java com/caverock/androidsvg/SVGImageView.java com/caverock/androidsvg/SVGParser.java com/caverock/androidsvg/SimpleAssetResolver.java com/github/penfeizhou/animation/FrameAnimationDrawable.java</p>

NO	ISSUE	SEVERITY	STANDARDS	FILES
1	The App logs information. Sensitive information should never be logged.	info	CWE: CWE-532: Insertion of Sensitive Information into Log File OWASP MASVS: MSTG-STORAGE-3	com/github/penfeizhou/animation/apng/decode/APNGDecoder.java com/github/penfeizhou/animation/decode/FrameSequenceDecoder.java com/github/penfeizhou/animation/gif/decode/GifDecoder.java com/horcrux/svg/Brush.java com/horcrux/svg/ClipPathView.java com/horcrux/svg/FilterView.java com/horcrux/svg/ImageView.java com/horcrux/svg/LinearGradientView.java com/horcrux/svg/PatternView.java com/horcrux/svg/RadialGradientView.java com/horcrux/svg/SvgViewManager.java com/horcrux/svg/UseView.java com/horcrux/svg/VirtualView.java com/reactcommunity/rndatetimepicker/Common.java com/reactcommunity/rndatetimepicker/MinuteIntervalSnappableTimePickerDialog.java com/reactnativecommunity/asyncstorage/AsyncLocalStorageUtil.java com/reactnativecommunity/asyncstorage/AsyncStorageExpoMigration.java com/reactnativecommunity/asyncstorage/AsyncStorageModule.java com/reactnativecommunity/asyncstorage/ReactDatabaseSupplier.java com/reactnativecommunity/webview/RNCWebView.java com/reactnativecommunity/webview/RNCWebViewClient.java com/reactnativecommunity/webview/RNCWebViewManagerImpl.java com/reactnativekeyboardcontroller/log/Logger.java com/rnmaps/maps/FileUtil.java com/rnmaps/maps/MapGradientPolyline.java com/rnmaps/maps/MapTileProvider.java com/rnmaps/maps/MapTileWorker.java com/rnmaps/maps/MapUrlTile.java com/rnmaps/maps/MapView.java com/swmansion/gesturehandler/react/RNGestureHandlerModule.java com/swmansion/gesturehandler/react/RNGestureH

NO	ISSUE	SEVERITY	STANDARDS	FILES
				<p>andlerRootHelper.java com/swmansion/gesturehandler/react/RNGestureH andlerRootView.java com/swmansion/reanimated/NativeMethodsHelper. java com/swmansion/reanimated/ReanimatedModule.ja va com/swmansion/reanimated/ReanimatedUIManage rFactory.java com/swmansion/reanimated/keyboard/WindowsIns etsManager.java com/swmansion/reanimated/layoutReanimation/An imationsManager.java com/swmansion/reanimated/layoutReanimation/Re animatedNativeHierarchyManager.java com/swmansion/reanimated/layoutReanimation/Scr eensHelper.java com/swmansion/reanimated/layoutReanimation/Sh aredTransitionManager.java com/swmansion/reanimated/layoutReanimation/Ta bNavigatorObserver.java com/swmansion/reanimated/nativeProxy/NativePro xyCommon.java com/swmansion/reanimated/sensor/ReanimatedSe nsorContainer.java com/swmansion/rnscreens/InsetsObserverProxy.jav a com/swmansion/rnscreens/ScreenStackHeaderConfi gViewManager.java com/swmansion/rnscreens/ScreensModule.java com/swmansion/rnscreens/SearchBarManager.java com/swmansion/rnscreens/gamma/helpers/System DrawableKt.java com/swmansion/rnscreens/gamma/tabs/TabScreen ViewManager.java com/swmansion/rnscreens/utils/ScreenDummyLay outHelper.java com/th3rdwave/safeareacontext/SafeAreaView.java expo/modules/ExpoModulesPackage.java expo/modules/ReactActivityDelegateWrapper\$onDe stroy\$1.java expo/modules/ReactActivityDelegateWrapper\$onPa use\$1.java expo/modules/adapters/react/permissions/UMManagerM</p>

NO	ISSUE	SEVERITY	STANDARDS	FILES
				expo/modules/adapters/react/services/OnManagerModuleWrapper.java expo/modules/apploader/AppLoaderProvider.java expo/modules/asset/AssetModule\$downloadAsset\$2.java expo/modules/audio/AudioModule.java expo/modules/audio/AudioPlayer.java expo/modules/audio/service/AudioRecordingService.java expo/modules/clipboard/ClipboardModule.java expo/modules/constants/ConstantsService.java expo/modules/core/logging/OSLogHandler.java expo/modules/core/logging/PersistentFileLog.java expo/modules/fetch/ExpoFetchModule.java expo/modules/fetch/NativeResponse.java expo/modules/filesystem/legacy/FileSystemLegacyModule\$downloadResumableTask\$2.java expo/modules/filesystem/legacy/FileSystemLegacyModule.java expo/modules/image/ExpoImageView.java expo/modules/image/ImageViewWrapperTarget.java expo/modules/image/ThumbnailRequestCoordinatorExtensionKt.java expo/modules/image/events/GlideRequestListener.java expo/modules/imagepicker/ImagePickerUtilsKt.java expo/modules/localization/LocalizationModule.java expo/modules/location/LocationModule.java expo/modules/location/records/GeocodeResponse.java expo/modules/location/taskConsumers/GeofencingTaskConsumer.java expo/modules/location/taskConsumers/LocationTaskConsumer.java expo/modules/medialibrary/MediaLibraryUtils.java expo/modules/medialibrary/assets/AssetUtilsKt.java expo/modules/notifications/badge/BadgeHelper.java expo/modules/notifications/notifications/ArgumentsNotificationContentBuilder.java expo/modules/notifications/notifications/background/BackgroundRemoteNotificationTaskConsumer.java

NO	ISSUE	SEVERITY	STANDARDS	FILES
				expo/modules/notifications/notifications/model/NotificationContent.java expo/modules/notifications/notifications/presentation/builders/BaseNotificationBuilder.java expo/modules/notifications/notifications/presentation/builders/ExpoNotificationBuilder.java expo/modules/notifications/serverregistration/InstallationId.java expo/modules/notifications/service/NotificationsService.java expo/modules/notifications/service/delegates/ExpoHandlingDelegate.java expo/modules/notifications/service/delegates/ExpoNotificationLifecycleListener.java expo/modules/notifications/service/delegates/ExpoPresentationDelegate.java expo/modules/notifications/service/delegates/ExpoSchedulingDelegate.java expo/modules/securestore/SecureStoreModule.java expo/modules/updates/UpdatesConfiguration.java expo/modules/updates/UpdatesUtils.java expo/modules/updates/codesigning/CodeSigningConfiguration.java expo/modules/updates/db/Converters.java expo/modules/updates/db/Reaper.java expo/modules/updates/loader/FileDownloader.java expo/modules/updates/loader/LoaderFiles.java expo/modules/updates/manifest/EmbeddedManifestUtils.java expo/modules/updates/manifest/EmbeddedUpdate.java expo/modules/updates/manifest/ExpoUpdatesUpdate.java expo/modules/updates/manifest/ManifestMetadata.java expo/modules/updates/manifest/ResponseHeaderData.java expo/modules/updates/selectionpolicy/SelectionPolicies.java io/sentry/SystemOutLogger.java io/sentry/android/core/AndroidFatalLogger.java io/sentry/android/core/AndroidLogger.java io/sentry/android/core/SentryLogcatAdapter.java io/sentry/android/replay/WindowManagerSpy.java

NO	ISSUE	SEVERITY	STANDARDS	FILES
				io/sentry/android/replay/WindowSpy.java io/sentry/clientreport/ClientReportRecorder.java io/sentry/transport/StdoutTransport.java
				io/sentry/util/ScopesUtil.java me/leolin/shortcutbadger/ShortcutBadger.java
2	Files may contain hardcoded sensitive information like usernames, passwords,	warning	CWE: CWE-312: Cleartext Storage of Sensitive Information OWASP Top 10: M9: Reverse Engineering	coil3/intercept/EngineInterceptor.java coil3/memory/MemoryCache.java coil3/memory/MemoryCacheService.java coil3/request/ImageRequest.java coil3/request/Options.java coil3/request/SuccessResult.java coil3/transform/Transformation.java com/bumptech/glide/load/Option.java com/bumptech/glide/load/engine/DataCacheKey.java com/bumptech/glide/load/engine/EngineResource.java com/bumptech/glide/load/engine/ResourceCacheKey.java com/reactnativekeyboardcontroller/views/background/ImePackages.java com/swmansion/rnscreens/gamma/tabs/event/TabsHostNativeFocusChangeEvent.java expo/modules/adapters/react/NativeModulesProxy.java expo/modules/clipboard/GetImageOptions.java expo/modules/easclient/EASClientIDKt.java expo/modules/image/records/SourceMap.java expo/modules/imagepicker/ImagePickerModuleKt.java expo/modules/interfaces/permissions/PermissionsResponse.java expo/modules/location/taskConsumers/LocationTaskConsumer.java expo/modules/medialibrary/MediaLibraryPermissionPromiseWrapper.java expo/modules/medialibrary/next/permissions/MediaLibraryPermissionPromiseWrapper.java expo/modules/medialibrary/next/records/SortDescriptor.java expo/modules/notifications/notifications/ArgumentsNotificationContentBuilder.java

NO	ISSUE keys etc.	SEVERITY	OWASP MASVS: MSTG-STORAGE-14 STANDARDS	FILES expo/modules/notifications/notifications/backgroundRemoteNotificationTaskConsumer.java
				expo/modules/notifications/notifications/channels/serializers/NotificationsChannelGroupSerializer.java expo/modules/notifications/notifications/channels/serializers/NotificationsChannelSerializer.java expo/modules/notifications/notifications/presentation/builders/ExpoNotificationBuilder.java expo/modules/notifications/permissions/NotificationPermissionsModuleKt.java expo/modules/notifications/serverregistration/InstallationId.java expo/modules/notifications/service/NotificationsService.java expo/modules/notifications/service/delegates/ExpoPresentationDelegate.java expo/modules/notifications/tokens/PushTokenModuleKt.java expo/modules/updates/UpdatesConfiguration.java expo/modules/updates/UpdatesModule\$definition\$lambda\$18\$inlined\$Coroutine\$8.java expo/modules/updates/codesigning/CodeSigningAlgorithmKt.java expo/modules/updates/codesigning/ExpoProjectInformation.java expo/modules/updates/loader/SigningInfo.java expo/modules/webbrowser/OpenBrowserOptions.java expo/modules/webbrowser/WebBrowserModuleKt.java io/sentry/Baggage.java io/sentry/RequestDetailsResolver.java io/sentry/SpanDataConvention.java io/sentry/TraceContext.java io/sentry/protocol/User.java

NO	ISSUE	SEVERITY	STANDARDS	FILES
3	App can read/write to External Storage. Any App can read data written to External Storage.	warning	CWE: CWE-276: Incorrect Default Permissions OWASP Top 10: M2: Insecure Data Storage OWASP MASVS: MSTG-STORAGE-2	com/canhub/cropper/BitmapUtils.java com/reactnativecommunity/webview/RNCWebViewModuleImpl.java expo/modules/clipboard/ClipboardFileProvider.java expo/modules/medialibrary/MediaLibraryUtils.java expo/modules/medialibrary/assets/CreateAssetWithAlbumFile.java expo/modules/medialibrary/next/objects/album/Album.java expo/modules/medialibrary/next/objects/wrappers/MimeType.java expo/modules/medialibrary/next/objects/wrappers/RelativePath.java io/sentry/android/core/DeviceInfoUtil.java
4	App creates temp file. Sensitive information should never be written into a temp file.	warning	CWE: CWE-276: Incorrect Default Permissions OWASP Top 10: M2: Insecure Data Storage OWASP MASVS: MSTG-STORAGE-2	coil3/decode/SourceImageSource.java com/canhub/cropper/BitmapUtils.java com/reactnativecommunity/webview/RNCWebViewModuleImpl.java com/rnmaps/maps/FileUtil.java com/rnmaps/maps/MapModule.java io/sentry/react/RNSentryModuleImpl.java
5	App uses SQLite Database and execute raw SQL query. Untrusted user input in raw SQL queries can cause SQL Injection. Also sensitive information should be encrypted and written to the database.	warning	CWE: CWE-89: Improper Neutralization of Special Elements used in an SQL Command ('SQL Injection') OWASP Top 10: M7: Client Code Quality	com/reactnativecommunity/asyncstorage/AsyncLocalStorageUtil.java com/reactnativecommunity/asyncstorage/ReactDatabaseSupplier.java
6	MD5 is a weak hash known to have hash collisions.	warning	CWE: CWE-327: Use of a Broken or Risky Cryptographic Algorithm OWASP Top 10: M5: Insufficient Cryptography OWASP MASVS: MSTG-CRYPTO-4	expo/modules/asset/AssetModule.java expo/modules/asset/FileUtilsKt.java expo/modules/filesystem/FileSystemFile.java expo/modules/filesystem/legacy/FileSystemLegacyModule.java

NO	ISSUE	SEVERITY	STANDARDS	FILES
7	IP Address disclosure	warning	CWE: CWE-200: Information Exposure OWASP MASVS: MSTG-CODE-2	io/sentry/SpotlightIntegration.java
8	This App may request root (Super User) privileges.	warning	CWE: CWE-250: Execution with Unnecessary Privileges OWASP MASVS: MSTG-RESILIENCE-1	io/sentry/android/core/internal/util/RootChecker.java
9	This App may have root detection capabilities.	secure	OWASP MASVS: MSTG-RESILIENCE-1	expo/modules/device/DeviceModule.java io/sentry/android/core/DeviceInfoUtil.java io/sentry/android/core/internal/util/RootChecker.java
10	The App uses an insecure Random Number Generator.	warning	CWE: CWE-330: Use of Insufficiently Random Values OWASP Top 10: M5: Insufficient Cryptography OWASP MASVS: MSTG-CRYPTO-6	expo/modules/updates/UpdatesUtils.java
11	SHA-1 is a weak hash known to have hash collisions.	warning	CWE: CWE-327: Use of a Broken or Risky Cryptographic Algorithm OWASP Top 10: M5: Insufficient Cryptography OWASP MASVS: MSTG-CRYPTO-4	io/sentry/util/StringUtils.java
12	Remote WebView debugging is enabled.	high	CWE: CWE-919: Weaknesses in Mobile Applications OWASP Top 10: M1: Improper Platform Usage OWASP MASVS: MSTG-RESILIENCE-2	com/reactnativecommunity/webview/RNCWebViewManagerImpl.java
13	This app listens to Clipboard changes. Some malware also listen to Clipboard changes.	info	OWASP MASVS: MSTG-PLATFORM-4	expo/modules/clipboard/ClipboardModule.java
14	This App copies data to clipboard. Sensitive data should not be copied to clipboard as other applications can access it.	info	OWASP MASVS: MSTG-STORAGE-10	expo/modules/clipboard/ClipboardModule.java

SHARED LIBRARY BINARY ANALYSIS

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
1	arm64-v8a/libreactnative.so	<p>True info</p> <p>The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>Dynamic Shared Object (DSO) info</p> <p>The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.</p>	<p>True info</p> <p>This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>None info</p> <p>The binary does not have run-time search path or RPATH set.</p>	<p>None info</p> <p>The binary does not have RUNPATH set.</p>	<p>True info</p> <p>The binary has the following fortified functions: ['_strlen_chk', '_memcpy_chk', '_vsnprintf_chk', '_memset_chk', '_fwrite_chk', '_write_chk', '_strncat_chk']</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
2	arm64-v8a/libhermestooling.so	<p>True info</p> <p>The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>Dynamic Shared Object (DSO) info</p> <p>The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.</p>	<p>True info</p> <p>This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>None info</p> <p>The binary does not have run-time search path or RPATH set.</p>	<p>None info</p> <p>The binary does not have RUNPATH set.</p>	<p>True info</p> <p>The binary has the following fortified functions: ['_strlen_chk']</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
3	arm64-v8a/libavif_android.so	<p>True info</p> <p>The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>Dynamic Shared Object (DSO) info</p> <p>The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.</p>	<p>True info</p> <p>This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>None info</p> <p>The binary does not have run-time search path or RPATH set.</p>	<p>None info</p> <p>The binary does not have RUNPATH set.</p>	<p>False warning</p> <p>The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
4	arm64-v8a/libnative-imagetranscoder.so	<p>True info</p> <p>The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>Dynamic Shared Object (DSO) info</p> <p>The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.</p>	<p>True info</p> <p>This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>None info</p> <p>The binary does not have run-time search path or RPATH set.</p>	<p>None info</p> <p>The binary does not have RUNPATH set.</p>	<p>True info</p> <p>The binary has the following fortified functions: ['_vsprintf_chk', '__strlen_chk', '__memcpy_chk']</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
5	arm64-v8a/libfbjni.so	<p>True info</p> <p>The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>Dynamic Shared Object (DSO) info</p> <p>The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.</p>	<p>True info</p> <p>This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>None info</p> <p>The binary does not have run-time search path or RPATH set.</p>	<p>None info</p> <p>The binary does not have RUNPATH set.</p>	<p>False warning</p> <p>The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
6	arm64-v8a/libc++_shared.so	<p>True info</p> <p>The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>Dynamic Shared Object (DSO) info</p> <p>The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.</p>	<p>False high</p> <p>This binary does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option -fstack-protector-all to enable stack canaries. Not applicable for Dart/Flutter libraries unless Dart FFI is used.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>None info</p> <p>The binary does not have run-time search path or RPATH set.</p>	<p>None info</p> <p>The binary does not have RUNPATH set.</p>	<p>False warning</p> <p>The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
7	arm64-v8a/libhermes.so	<p>True info</p> <p>The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>Dynamic Shared Object (DSO) info</p> <p>The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.</p>	<p>True info</p> <p>This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>None info</p> <p>The binary does not have run-time search path or RPATH set.</p>	<p>None info</p> <p>The binary does not have RUNPATH set.</p>	<p>True info</p> <p>The binary has the following fortified functions: ['_memcpy_chk', '_write_chk', '_strlen_chk', '_vsnprintf_chk', '_strchr_chk']</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
8	arm64-v8a/libnative-filters.so	<p>True info</p> <p>The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>Dynamic Shared Object (DSO) info</p> <p>The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.</p>	<p>True info</p> <p>This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>None info</p> <p>The binary does not have run-time search path or RPATH set.</p>	<p>None info</p> <p>The binary does not have RUNPATH set.</p>	<p>False warning</p> <p>The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
9	arm64-v8a/libanimation-decoder-gif.so	<p>True info</p> <p>The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>Dynamic Shared Object (DSO) info</p> <p>The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.</p>	<p>True info</p> <p>This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>None info</p> <p>The binary does not have run-time search path or RPATH set.</p>	<p>None info</p> <p>The binary does not have RUNPATH set.</p>	<p>False warning</p> <p>The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
10	arm64-v8a/librnscreens.so	<p>True info</p> <p>The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>Dynamic Shared Object (DSO) info</p> <p>The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.</p>	<p>True info</p> <p>This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>None info</p> <p>The binary does not have run-time search path or RPATH set.</p>	<p>None info</p> <p>The binary does not have RUNPATH set.</p>	<p>False warning</p> <p>The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
11	arm64-v8a/libsoentry.so	<p>True info</p> <p>The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>Dynamic Shared Object (DSO) info</p> <p>The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.</p>	<p>True info</p> <p>This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>None info</p> <p>The binary does not have run-time search path or RPATH set.</p>	<p>None info</p> <p>The binary does not have RUNPATH set.</p>	<p>True info</p> <p>The binary has the following fortified functions: ['_vsnprintf_chk', '__read_chk', '__memmove_chk', '__strncpy_chk', '__strlen_chk', '__memcpy_chk']</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
12	arm64-v8a/libexpo-modules-core.so	<p>True info</p> <p>The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>Dynamic Shared Object (DSO) info</p> <p>The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.</p>	<p>True info</p> <p>This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>None info</p> <p>The binary does not have run-time search path or RPATH set.</p>	<p>None info</p> <p>The binary does not have RUNPATH set.</p>	<p>True info</p> <p>The binary has the following fortified functions: ['_strlen_chk']</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
13	arm64-v8a/libgifimage.so	<p>True info</p> <p>The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>Dynamic Shared Object (DSO) info</p> <p>The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.</p>	<p>True info</p> <p>This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>None info</p> <p>The binary does not have run-time search path or RPATH set.</p>	<p>None info</p> <p>The binary does not have RUNPATH set.</p>	<p>False warning</p> <p>The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
14	arm64-v8a/libimagepipeline.so	<p>True info</p> <p>The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>Dynamic Shared Object (DSO) info</p> <p>The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.</p>	<p>True info</p> <p>This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>None info</p> <p>The binary does not have run-time search path or RPATH set.</p>	<p>None info</p> <p>The binary does not have RUNPATH set.</p>	<p>False warning</p> <p>The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
15	arm64-v8a/libworklets.so	<p>True info</p> <p>The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>Dynamic Shared Object (DSO) info</p> <p>The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.</p>	<p>True info</p> <p>This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>None info</p> <p>The binary does not have run-time search path or RPATH set.</p>	<p>None info</p> <p>The binary does not have RUNPATH set.</p>	<p>True info</p> <p>The binary has the following fortified functions: ['_strlen_chk']</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
16	arm64-v8a/libjsi.so	<p>True info</p> <p>The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>Dynamic Shared Object (DSO) info</p> <p>The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.</p>	<p>True info</p> <p>This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>None info</p> <p>The binary does not have run-time search path or RPATH set.</p>	<p>None info</p> <p>The binary does not have RUNPATH set.</p>	<p>True info</p> <p>The binary has the following fortified functions: ['_memcpy_chk', '_strlen_chk', '_memset_chk', '_vsnprintf_chk', '_fwrite_chk', '_write_chk', '_strncat_chk']</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
17	arm64-v8a/libstatic-webp.so	<p>True info</p> <p>The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>Dynamic Shared Object (DSO) info</p> <p>The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.</p>	<p>True info</p> <p>This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>None info</p> <p>The binary does not have run-time search path or RPATH set.</p>	<p>None info</p> <p>The binary does not have RUNPATH set.</p>	<p>True info</p> <p>The binary has the following fortified functions: ['_memcpy_chk']</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
18	arm64-v8a/libreanimated.so	<p>True info</p> <p>The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>Dynamic Shared Object (DSO) info</p> <p>The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.</p>	<p>True info</p> <p>This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>None info</p> <p>The binary does not have run-time search path or RPATH set.</p>	<p>None info</p> <p>The binary does not have RUNPATH set.</p>	<p>True info</p> <p>The binary has the following fortified functions: ['_strlen_chk']</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
19	arm64-v8a/libsendry-android.so	<p>True info</p> <p>The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>Dynamic Shared Object (DSO) info</p> <p>The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.</p>	<p>True info</p> <p>This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>None info</p> <p>The binary does not have run-time search path or RPATH set.</p>	<p>None info</p> <p>The binary does not have RUNPATH set.</p>	<p>True info</p> <p>The binary has the following fortified functions: ['_vsprintf_chk']</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
20	x86_64/libreactnative.so	<p>True info</p> <p>The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>Dynamic Shared Object (DSO) info</p> <p>The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.</p>	<p>True info</p> <p>This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>None info</p> <p>The binary does not have run-time search path or RPATH set.</p>	<p>None info</p> <p>The binary does not have RUNPATH set.</p>	<p>True info</p> <p>The binary has the following fortified functions: ['_strlen_chk', '_memcpy_chk', '_vsprintf_chk', '_memset_chk', '_fwrite_chk', '_write_chk', '_strncat_chk']</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
21	x86_64/libhermestooling.so	<p>True info</p> <p>The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>Dynamic Shared Object (DSO) info</p> <p>The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.</p>	<p>True info</p> <p>This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>None info</p> <p>The binary does not have run-time search path or RPATH set.</p>	<p>None info</p> <p>The binary does not have RUNPATH set.</p>	<p>True info</p> <p>The binary has the following fortified functions: ['_strlen_chk']</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
22	x86_64/libavif_android.so	<p>True info</p> <p>The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>Dynamic Shared Object (DSO) info</p> <p>The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.</p>	<p>True info</p> <p>This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>None info</p> <p>The binary does not have run-time search path or RPATH set.</p>	<p>None info</p> <p>The binary does not have RUNPATH set.</p>	<p>False warning</p> <p>The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
23	x86_64/libnative-imagetranscoder.so	<p>True info</p> <p>The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>Dynamic Shared Object (DSO) info</p> <p>The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.</p>	<p>True info</p> <p>This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>None info</p> <p>The binary does not have run-time search path or RPATH set.</p>	<p>None info</p> <p>The binary does not have RUNPATH set.</p>	<p>True info</p> <p>The binary has the following fortified functions: ['_vsprintf_chk', '_strlen_chk']</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
24	x86_64/libfbjni.so	<p>True info</p> <p>The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>Dynamic Shared Object (DSO) info</p> <p>The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.</p>	<p>True info</p> <p>This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>None info</p> <p>The binary does not have run-time search path or RPATH set.</p>	<p>None info</p> <p>The binary does not have RUNPATH set.</p>	<p>False warning</p> <p>The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
25	x86_64/libc++_shared.so	<p>True info</p> <p>The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>Dynamic Shared Object (DSO) info</p> <p>The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.</p>	<p>False high</p> <p>This binary does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option -fstack-protector-all to enable stack canaries. Not applicable for Dart/Flutter libraries unless Dart FFI is used.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>None info</p> <p>The binary does not have run-time search path or RPATH set.</p>	<p>None info</p> <p>The binary does not have RUNPATH set.</p>	<p>False warning</p> <p>The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
26	x86_64/libhermes.so	<p>True info</p> <p>The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>Dynamic Shared Object (DSO) info</p> <p>The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.</p>	<p>True info</p> <p>This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>None info</p> <p>The binary does not have run-time search path or RPATH set.</p>	<p>None info</p> <p>The binary does not have RUNPATH set.</p>	<p>True info</p> <p>The binary has the following fortified functions: ['_write_chk', '_strlen_chk', '_vsnprintf_chk', '_strchr_chk']</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
27	x86_64/libnative-filters.so	<p>True info</p> <p>The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>Dynamic Shared Object (DSO) info</p> <p>The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.</p>	<p>True info</p> <p>This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>None info</p> <p>The binary does not have run-time search path or RPATH set.</p>	<p>None info</p> <p>The binary does not have RUNPATH set.</p>	<p>False warning</p> <p>The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
28	x86_64/libanimation-decoder-gif.so	<p>True info</p> <p>The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>Dynamic Shared Object (DSO) info</p> <p>The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.</p>	<p>True info</p> <p>This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>None info</p> <p>The binary does not have run-time search path or RPATH set.</p>	<p>None info</p> <p>The binary does not have RUNPATH set.</p>	<p>False warning</p> <p>The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
29	x86_64/librnscreens.so	<p>True info</p> <p>The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>Dynamic Shared Object (DSO) info</p> <p>The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.</p>	<p>True info</p> <p>This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>None info</p> <p>The binary does not have run-time search path or RPATH set.</p>	<p>None info</p> <p>The binary does not have RUNPATH set.</p>	<p>False warning</p> <p>The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
30	x86_64/libentry.so	<p>True info</p> <p>The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>Dynamic Shared Object (DSO) info</p> <p>The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.</p>	<p>True info</p> <p>This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>None info</p> <p>The binary does not have run-time search path or RPATH set.</p>	<p>None info</p> <p>The binary does not have RUNPATH set.</p>	<p>True info</p> <p>The binary has the following fortified functions: ['_vsprintf_chk', '_read_chk', '_memmove_chk', '_strncpy_chk', '_strlen_chk', '_memcpy_chk']</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
31	x86_64/libexpo-modules-core.so	<p>True info</p> <p>The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>Dynamic Shared Object (DSO) info</p> <p>The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.</p>	<p>True info</p> <p>This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>None info</p> <p>The binary does not have run-time search path or RPATH set.</p>	<p>None info</p> <p>The binary does not have RUNPATH set.</p>	<p>True info</p> <p>The binary has the following fortified functions: ['_strlen_chk']</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
32	x86_64/libgifimage.so	<p>True info</p> <p>The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>Dynamic Shared Object (DSO) info</p> <p>The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.</p>	<p>True info</p> <p>This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>None info</p> <p>The binary does not have run-time search path or RPATH set.</p>	<p>None info</p> <p>The binary does not have RUNPATH set.</p>	<p>False warning</p> <p>The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
33	x86_64/libimagepipeline.so	<p>True info</p> <p>The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>Dynamic Shared Object (DSO) info</p> <p>The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.</p>	<p>True info</p> <p>This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>None info</p> <p>The binary does not have run-time search path or RPATH set.</p>	<p>None info</p> <p>The binary does not have RUNPATH set.</p>	<p>False warning</p> <p>The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
34	x86_64/libworklets.so	<p>True info</p> <p>The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>Dynamic Shared Object (DSO) info</p> <p>The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.</p>	<p>True info</p> <p>This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>None info</p> <p>The binary does not have run-time search path or RPATH set.</p>	<p>None info</p> <p>The binary does not have RUNPATH set.</p>	<p>True info</p> <p>The binary has the following fortified functions: ['_strlen_chk']</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
35	x86_64/libjsi.so	<p>True info</p> <p>The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>Dynamic Shared Object (DSO) info</p> <p>The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.</p>	<p>True info</p> <p>This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>None info</p> <p>The binary does not have run-time search path or RPATH set.</p>	<p>None info</p> <p>The binary does not have RUNPATH set.</p>	<p>True info</p> <p>The binary has the following fortified functions: ['_memcpy_chk', '_strlen_chk', '_memset_chk', '_vsnprintf_chk', '_fwrite_chk', '_write_chk', '_strncat_chk']</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
36	x86_64/libstatic-webp.so	<p>True info</p> <p>The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>Dynamic Shared Object (DSO) info</p> <p>The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.</p>	<p>True info</p> <p>This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>None info</p> <p>The binary does not have run-time search path or RPATH set.</p>	<p>None info</p> <p>The binary does not have RUNPATH set.</p>	<p>True info</p> <p>The binary has the following fortified functions: ['_memcpy_chk']</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
37	x86_64/libreanimated.so	<p>True info</p> <p>The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>Dynamic Shared Object (DSO) info</p> <p>The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.</p>	<p>True info</p> <p>This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>None info</p> <p>The binary does not have run-time search path or RPATH set.</p>	<p>None info</p> <p>The binary does not have RUNPATH set.</p>	<p>True info</p> <p>The binary has the following fortified functions: ['_strlen_chk']</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
38	x86_64/lib Sentry-android.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['_vsprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
39	armeabi-v7a/libreactnative.so	<p>True info</p> <p>The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>Dynamic Shared Object (DSO) info</p> <p>The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.</p>	<p>True info</p> <p>This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>None info</p> <p>The binary does not have run-time search path or RPATH set.</p>	<p>None info</p> <p>The binary does not have RUNPATH set.</p>	<p>True info</p> <p>The binary has the following fortified functions: ['_strlen_chk', '_memcpy_chk', '_vsprintf_chk', '_memset_chk', '_fwrite_chk', '_write_chk', '_strncat_chk']</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
40	armeabi-v7a/libhermestooling.so	<p>True info</p> <p>The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>Dynamic Shared Object (DSO) info</p> <p>The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.</p>	<p>True info</p> <p>This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>None info</p> <p>The binary does not have run-time search path or RPATH set.</p>	<p>None info</p> <p>The binary does not have RUNPATH set.</p>	<p>True info</p> <p>The binary has the following fortified functions: ['_strlen_chk']</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
41	armeabi-v7a/libavif_android.so	<p>True info</p> <p>The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>Dynamic Shared Object (DSO) info</p> <p>The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.</p>	<p>True info</p> <p>This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>None info</p> <p>The binary does not have run-time search path or RPATH set.</p>	<p>None info</p> <p>The binary does not have RUNPATH set.</p>	<p>False warning</p> <p>The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
42	armeabi-v7a/libnative-imagetranscoder.so	<p>True info</p> <p>The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>Dynamic Shared Object (DSO) info</p> <p>The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.</p>	<p>True info</p> <p>This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>None info</p> <p>The binary does not have run-time search path or RPATH set.</p>	<p>None info</p> <p>The binary does not have RUNPATH set.</p>	<p>True info</p> <p>The binary has the following fortified functions: ['_vsprintf_chk', '_strlen_chk', '_memcpy_chk']</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
43	armeabi-v7a/libfbjni.so	<p>True info</p> <p>The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>Dynamic Shared Object (DSO) info</p> <p>The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.</p>	<p>True info</p> <p>This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>None info</p> <p>The binary does not have run-time search path or RPATH set.</p>	<p>None info</p> <p>The binary does not have RUNPATH set.</p>	<p>False warning</p> <p>The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
44	armeabi-v7a/libc++_shared.so	<p>True info</p> <p>The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>Dynamic Shared Object (DSO) info</p> <p>The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.</p>	<p>False high</p> <p>This binary does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option -fstack-protector-all to enable stack canaries. Not applicable for Dart/Flutter libraries unless Dart FFI is used.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>None info</p> <p>The binary does not have run-time search path or RPATH set.</p>	<p>None info</p> <p>The binary does not have RUNPATH set.</p>	<p>False warning</p> <p>The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
45	armeabi-v7a/libhermes.so	<p>True info</p> <p>The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>Dynamic Shared Object (DSO) info</p> <p>The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.</p>	<p>True info</p> <p>This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>None info</p> <p>The binary does not have run-time search path or RPATH set.</p>	<p>None info</p> <p>The binary does not have RUNPATH set.</p>	<p>True info</p> <p>The binary has the following fortified functions: ['_write_chk', '_strlen_chk', '_vsprintf_chk', '_strchr_chk']</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
46	armeabi-v7a/libnative-filters.so	<p>True info</p> <p>The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>Dynamic Shared Object (DSO) info</p> <p>The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.</p>	<p>True info</p> <p>This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>None info</p> <p>The binary does not have run-time search path or RPATH set.</p>	<p>None info</p> <p>The binary does not have RUNPATH set.</p>	<p>False warning</p> <p>The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
47	armeabi-v7a/libanimation-decoder-gif.so	<p>True info</p> <p>The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>Dynamic Shared Object (DSO) info</p> <p>The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.</p>	<p>True info</p> <p>This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>None info</p> <p>The binary does not have run-time search path or RPATH set.</p>	<p>None info</p> <p>The binary does not have RUNPATH set.</p>	<p>False warning</p> <p>The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
48	armeabi-v7a/librnscreens.so	<p>True info</p> <p>The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>Dynamic Shared Object (DSO) info</p> <p>The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.</p>	<p>True info</p> <p>This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>None info</p> <p>The binary does not have run-time search path or RPATH set.</p>	<p>None info</p> <p>The binary does not have RUNPATH set.</p>	<p>False warning</p> <p>The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
49	armeabi-v7a/lib Sentry.so	<p>True info</p> <p>The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>Dynamic Shared Object (DSO) info</p> <p>The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.</p>	<p>True info</p> <p>This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>None info</p> <p>The binary does not have run-time search path or RPATH set.</p>	<p>None info</p> <p>The binary does not have RUNPATH set.</p>	<p>True info</p> <p>The binary has the following fortified functions: ['_vsprintf_chk', '__read_chk', '__memmove_chk', '__strncpy_chk', '__strlen_chk', '__memcpy_chk']</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
50	armeabi-v7a/libexpo-modules-core.so	<p>True info</p> <p>The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>Dynamic Shared Object (DSO) info</p> <p>The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.</p>	<p>True info</p> <p>This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>None info</p> <p>The binary does not have run-time search path or RPATH set.</p>	<p>None info</p> <p>The binary does not have RUNPATH set.</p>	<p>True info</p> <p>The binary has the following fortified functions: ['_strlen_chk', '_vsprintf_chk']</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
51	armeabi-v7a/libgifimage.so	<p>True info</p> <p>The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>Dynamic Shared Object (DSO) info</p> <p>The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.</p>	<p>True info</p> <p>This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>None info</p> <p>The binary does not have run-time search path or RPATH set.</p>	<p>None info</p> <p>The binary does not have RUNPATH set.</p>	<p>True info</p> <p>The binary has the following fortified functions: ['_vsnprintf_chk']</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
52	armeabi-v7a/libimagepipeline.so	<p>True info</p> <p>The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>Dynamic Shared Object (DSO) info</p> <p>The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.</p>	<p>True info</p> <p>This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>None info</p> <p>The binary does not have run-time search path or RPATH set.</p>	<p>None info</p> <p>The binary does not have RUNPATH set.</p>	<p>False warning</p> <p>The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
53	armeabi-v7a/libworklets.so	<p>True info</p> <p>The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>Dynamic Shared Object (DSO) info</p> <p>The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.</p>	<p>True info</p> <p>This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>None info</p> <p>The binary does not have run-time search path or RPATH set.</p>	<p>None info</p> <p>The binary does not have RUNPATH set.</p>	<p>True info</p> <p>The binary has the following fortified functions: ['_strlen_chk']</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
54	armeabi-v7a/libjsi.so	<p>True info</p> <p>The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>Dynamic Shared Object (DSO) info</p> <p>The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.</p>	<p>True info</p> <p>This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>None info</p> <p>The binary does not have run-time search path or RPATH set.</p>	<p>None info</p> <p>The binary does not have RUNPATH set.</p>	<p>True info</p> <p>The binary has the following fortified functions: ['_memcpy_chk', '_strlen_chk', '_vsprintf_chk', '_memset_chk', '_fwrite_chk', '_write_chk', '_strncat_chk']</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
55	armeabi-v7a/libstatic-webp.so	<p>True info</p> <p>The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>Dynamic Shared Object (DSO) info</p> <p>The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.</p>	<p>True info</p> <p>This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>None info</p> <p>The binary does not have run-time search path or RPATH set.</p>	<p>None info</p> <p>The binary does not have RUNPATH set.</p>	<p>True info</p> <p>The binary has the following fortified functions: ['_vsprintf_chk', '_memcpy_chk']</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
56	armeabi-v7a/libreanimated.so	<p>True info</p> <p>The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>Dynamic Shared Object (DSO) info</p> <p>The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.</p>	<p>True info</p> <p>This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>None info</p> <p>The binary does not have run-time search path or RPATH set.</p>	<p>None info</p> <p>The binary does not have RUNPATH set.</p>	<p>True info</p> <p>The binary has the following fortified functions: ['_strlen_chk', '_vsprintf_chk']</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
57	armeabi-v7a/libentry-android.so	<p>True info</p> <p>The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>Dynamic Shared Object (DSO) info</p> <p>The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.</p>	<p>True info</p> <p>This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>None info</p> <p>The binary does not have run-time search path or RPATH set.</p>	<p>None info</p> <p>The binary does not have RUNPATH set.</p>	<p>True info</p> <p>The binary has the following fortified functions: ['_vsprintf_chk']</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
58	x86/libreactnative.so	<p>True info</p> <p>The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>Dynamic Shared Object (DSO) info</p> <p>The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.</p>	<p>True info</p> <p>This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>None info</p> <p>The binary does not have run-time search path or RPATH set.</p>	<p>None info</p> <p>The binary does not have RUNPATH set.</p>	<p>True info</p> <p>The binary has the following fortified functions: ['_strlen_chk', '_memcpy_chk', '_vsprintf_chk', '_memset_chk', '_fwrite_chk', '_write_chk', '_strncat_chk']</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
59	x86/libhermestooling.so	<p>True info</p> <p>The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>Dynamic Shared Object (DSO) info</p> <p>The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.</p>	<p>True info</p> <p>This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>None info</p> <p>The binary does not have run-time search path or RPATH set.</p>	<p>None info</p> <p>The binary does not have RUNPATH set.</p>	<p>True info</p> <p>The binary has the following fortified functions: ['_strlen_chk']</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
60	x86/libavif_android.so	<p>True info</p> <p>The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>Dynamic Shared Object (DSO) info</p> <p>The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.</p>	<p>True info</p> <p>This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>None info</p> <p>The binary does not have run-time search path or RPATH set.</p>	<p>None info</p> <p>The binary does not have RUNPATH set.</p>	<p>False warning</p> <p>The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
61	x86/libnative-imagetranscoder.so	<p>True info</p> <p>The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>Dynamic Shared Object (DSO) info</p> <p>The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.</p>	<p>True info</p> <p>This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>None info</p> <p>The binary does not have run-time search path or RPATH set.</p>	<p>None info</p> <p>The binary does not have RUNPATH set.</p>	<p>True info</p> <p>The binary has the following fortified functions: ['_vsprintf_chk', '_strlen_chk']</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
62	x86/libfbjni.so	<p>True info</p> <p>The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>Dynamic Shared Object (DSO) info</p> <p>The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.</p>	<p>True info</p> <p>This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>None info</p> <p>The binary does not have run-time search path or RPATH set.</p>	<p>None info</p> <p>The binary does not have RUNPATH set.</p>	<p>False warning</p> <p>The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
63	x86/libc++_shared.so	<p>True info</p> <p>The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>Dynamic Shared Object (DSO) info</p> <p>The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.</p>	<p>False high</p> <p>This binary does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option -fstack-protector-all to enable stack canaries. Not applicable for Dart/Flutter libraries unless Dart FFI is used.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>None info</p> <p>The binary does not have run-time search path or RPATH set.</p>	<p>None info</p> <p>The binary does not have RUNPATH set.</p>	<p>False warning</p> <p>The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
64	x86/libhermes.so	<p>True info</p> <p>The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>Dynamic Shared Object (DSO) info</p> <p>The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.</p>	<p>True info</p> <p>This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>None info</p> <p>The binary does not have run-time search path or RPATH set.</p>	<p>None info</p> <p>The binary does not have RUNPATH set.</p>	<p>True info</p> <p>The binary has the following fortified functions: ['_write_chk', '_strlen_chk', '_vsprintf_chk', '_strchr_chk']</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
65	x86/libnative-filters.so	<p>True info</p> <p>The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>Dynamic Shared Object (DSO) info</p> <p>The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.</p>	<p>True info</p> <p>This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>None info</p> <p>The binary does not have run-time search path or RPATH set.</p>	<p>None info</p> <p>The binary does not have RUNPATH set.</p>	<p>False warning</p> <p>The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
66	x86/libanimation-decoder-gif.so	<p>True info</p> <p>The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>Dynamic Shared Object (DSO) info</p> <p>The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.</p>	<p>True info</p> <p>This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>None info</p> <p>The binary does not have run-time search path or RPATH set.</p>	<p>None info</p> <p>The binary does not have RUNPATH set.</p>	<p>False warning</p> <p>The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
67	x86/librnscreens.so	<p>True info</p> <p>The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>Dynamic Shared Object (DSO) info</p> <p>The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.</p>	<p>True info</p> <p>This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>None info</p> <p>The binary does not have run-time search path or RPATH set.</p>	<p>None info</p> <p>The binary does not have RUNPATH set.</p>	<p>False warning</p> <p>The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
68	x86/libsentry.so	<p>True info</p> <p>The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>Dynamic Shared Object (DSO) info</p> <p>The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.</p>	<p>True info</p> <p>This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>None info</p> <p>The binary does not have run-time search path or RPATH set.</p>	<p>None info</p> <p>The binary does not have RUNPATH set.</p>	<p>True info</p> <p>The binary has the following fortified functions: ['_vsnprintf_chk', '__read_chk', '__memmove_chk', '__strncpy_chk', '__strlen_chk', '__memcpy_chk']</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
69	x86/libexpo-modules-core.so	<p>True info</p> <p>The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>Dynamic Shared Object (DSO) info</p> <p>The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.</p>	<p>True info</p> <p>This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>None info</p> <p>The binary does not have run-time search path or RPATH set.</p>	<p>None info</p> <p>The binary does not have RUNPATH set.</p>	<p>True info</p> <p>The binary has the following fortified functions: ['_strlen_chk']</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
70	x86/libgifimage.so	<p>True info</p> <p>The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>Dynamic Shared Object (DSO) info</p> <p>The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.</p>	<p>True info</p> <p>This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>None info</p> <p>The binary does not have run-time search path or RPATH set.</p>	<p>None info</p> <p>The binary does not have RUNPATH set.</p>	<p>False warning</p> <p>The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
71	x86/libimagepipeline.so	<p>True info</p> <p>The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>Dynamic Shared Object (DSO) info</p> <p>The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.</p>	<p>True info</p> <p>This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>None info</p> <p>The binary does not have run-time search path or RPATH set.</p>	<p>None info</p> <p>The binary does not have RUNPATH set.</p>	<p>False warning</p> <p>The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
72	x86/libworklets.so	<p>True info</p> <p>The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>Dynamic Shared Object (DSO) info</p> <p>The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.</p>	<p>True info</p> <p>This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>None info</p> <p>The binary does not have run-time search path or RPATH set.</p>	<p>None info</p> <p>The binary does not have RUNPATH set.</p>	<p>True info</p> <p>The binary has the following fortified functions: ['_strlen_chk']</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
73	x86/libjsi.so	<p>True info</p> <p>The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>Dynamic Shared Object (DSO) info</p> <p>The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.</p>	<p>True info</p> <p>This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>None info</p> <p>The binary does not have run-time search path or RPATH set.</p>	<p>None info</p> <p>The binary does not have RUNPATH set.</p>	<p>True info</p> <p>The binary has the following fortified functions: ['_memcpy_chk', '_strlen_chk', '_memset_chk', '_vsnprintf_chk', '_fwrite_chk', '_write_chk', '_strncat_chk']</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
74	x86/libstatic-webp.so	<p>True info</p> <p>The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>Dynamic Shared Object (DSO) info</p> <p>The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.</p>	<p>True info</p> <p>This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>None info</p> <p>The binary does not have run-time search path or RPATH set.</p>	<p>None info</p> <p>The binary does not have RUNPATH set.</p>	<p>True info</p> <p>The binary has the following fortified functions: ['_memcpy_chk']</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
75	x86/libreanimated.so	<p>True info</p> <p>The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>Dynamic Shared Object (DSO) info</p> <p>The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.</p>	<p>True info</p> <p>This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>None info</p> <p>The binary does not have run-time search path or RPATH set.</p>	<p>None info</p> <p>The binary does not have RUNPATH set.</p>	<p>True info</p> <p>The binary has the following fortified functions: ['_strlen_chk']</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
76	x86/libentry-android.so	<p>True info</p> <p>The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>Dynamic Shared Object (DSO) info</p> <p>The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.</p>	<p>True info</p> <p>This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>None info</p> <p>The binary does not have run-time search path or RPATH set.</p>	<p>None info</p> <p>The binary does not have RUNPATH set.</p>	<p>True info</p> <p>The binary has the following fortified functions: ['_vsprintf_chk']</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
77	arm64-v8a/libreactnative.so	<p>True info</p> <p>The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>Dynamic Shared Object (DSO) info</p> <p>The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.</p>	<p>True info</p> <p>This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>None info</p> <p>The binary does not have run-time search path or RPATH set.</p>	<p>None info</p> <p>The binary does not have RUNPATH set.</p>	<p>True info</p> <p>The binary has the following fortified functions: ['_strlen_chk', '_memcpy_chk', '_vsprintf_chk', '_memset_chk', '_fwrite_chk', '_write_chk', '_strncat_chk']</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
78	arm64-v8a/libhermestooling.so	<p>True info</p> <p>The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>Dynamic Shared Object (DSO) info</p> <p>The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.</p>	<p>True info</p> <p>This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>None info</p> <p>The binary does not have run-time search path or RPATH set.</p>	<p>None info</p> <p>The binary does not have RUNPATH set.</p>	<p>True info</p> <p>The binary has the following fortified functions: ['_strlen_chk']</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
79	arm64-v8a/libavif_android.so	<p>True info</p> <p>The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>Dynamic Shared Object (DSO) info</p> <p>The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.</p>	<p>True info</p> <p>This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>None info</p> <p>The binary does not have run-time search path or RPATH set.</p>	<p>None info</p> <p>The binary does not have RUNPATH set.</p>	<p>False warning</p> <p>The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
80	arm64-v8a/libnative-imagetranscoder.so	<p>True info</p> <p>The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>Dynamic Shared Object (DSO) info</p> <p>The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.</p>	<p>True info</p> <p>This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>None info</p> <p>The binary does not have run-time search path or RPATH set.</p>	<p>None info</p> <p>The binary does not have RUNPATH set.</p>	<p>True info</p> <p>The binary has the following fortified functions: ['_vsprintf_chk', '_strlen_chk', '_memcpy_chk']</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
81	arm64-v8a/libfbjni.so	<p>True info</p> <p>The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>Dynamic Shared Object (DSO) info</p> <p>The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.</p>	<p>True info</p> <p>This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>None info</p> <p>The binary does not have run-time search path or RPATH set.</p>	<p>None info</p> <p>The binary does not have RUNPATH set.</p>	<p>False warning</p> <p>The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
82	arm64-v8a/libc++_shared.so	<p>True info</p> <p>The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>Dynamic Shared Object (DSO) info</p> <p>The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.</p>	<p>False high</p> <p>This binary does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option -fstack-protector-all to enable stack canaries. Not applicable for Dart/Flutter libraries unless Dart FFI is used.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>None info</p> <p>The binary does not have run-time search path or RPATH set.</p>	<p>None info</p> <p>The binary does not have RUNPATH set.</p>	<p>False warning</p> <p>The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
83	arm64-v8a/libhermes.so	<p>True info</p> <p>The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>Dynamic Shared Object (DSO) info</p> <p>The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.</p>	<p>True info</p> <p>This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>None info</p> <p>The binary does not have run-time search path or RPATH set.</p>	<p>None info</p> <p>The binary does not have RUNPATH set.</p>	<p>True info</p> <p>The binary has the following fortified functions: ['_memcpy_chk', '_write_chk', '_strlen_chk', '_vsprintf_chk', '_strchr_chk']</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
84	arm64-v8a/libnative-filters.so	<p>True info</p> <p>The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>Dynamic Shared Object (DSO) info</p> <p>The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.</p>	<p>True info</p> <p>This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>None info</p> <p>The binary does not have run-time search path or RPATH set.</p>	<p>None info</p> <p>The binary does not have RUNPATH set.</p>	<p>False warning</p> <p>The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
85	arm64-v8a/libanimation-decoder-gif.so	<p>True info</p> <p>The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>Dynamic Shared Object (DSO) info</p> <p>The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.</p>	<p>True info</p> <p>This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>None info</p> <p>The binary does not have run-time search path or RPATH set.</p>	<p>None info</p> <p>The binary does not have RUNPATH set.</p>	<p>False warning</p> <p>The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
86	arm64-v8a/librnscreens.so	<p>True info</p> <p>The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>Dynamic Shared Object (DSO) info</p> <p>The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.</p>	<p>True info</p> <p>This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>None info</p> <p>The binary does not have run-time search path or RPATH set.</p>	<p>None info</p> <p>The binary does not have RUNPATH set.</p>	<p>False warning</p> <p>The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
87	arm64-v8a/libsendentry.so	<p>True info</p> <p>The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>Dynamic Shared Object (DSO) info</p> <p>The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.</p>	<p>True info</p> <p>This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>None info</p> <p>The binary does not have run-time search path or RPATH set.</p>	<p>None info</p> <p>The binary does not have RUNPATH set.</p>	<p>True info</p> <p>The binary has the following fortified functions: ['_vsnprintf_chk', '__read_chk', '__memmove_chk', '__strncpy_chk', '__strlen_chk', '__memcpy_chk']</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
88	arm64-v8a/libexpo-modules-core.so	<p>True info</p> <p>The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>Dynamic Shared Object (DSO) info</p> <p>The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.</p>	<p>True info</p> <p>This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>None info</p> <p>The binary does not have run-time search path or RPATH set.</p>	<p>None info</p> <p>The binary does not have RUNPATH set.</p>	<p>True info</p> <p>The binary has the following fortified functions: ['_strlen_chk']</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
89	arm64-v8a/libgifimage.so	<p>True info</p> <p>The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>Dynamic Shared Object (DSO) info</p> <p>The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.</p>	<p>True info</p> <p>This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>None info</p> <p>The binary does not have run-time search path or RPATH set.</p>	<p>None info</p> <p>The binary does not have RUNPATH set.</p>	<p>False warning</p> <p>The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
90	arm64-v8a/libimagepipeline.so	<p>True info</p> <p>The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>Dynamic Shared Object (DSO) info</p> <p>The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.</p>	<p>True info</p> <p>This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>None info</p> <p>The binary does not have run-time search path or RPATH set.</p>	<p>None info</p> <p>The binary does not have RUNPATH set.</p>	<p>False warning</p> <p>The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
91	arm64-v8a/libworklets.so	<p>True info</p> <p>The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>Dynamic Shared Object (DSO) info</p> <p>The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.</p>	<p>True info</p> <p>This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>None info</p> <p>The binary does not have run-time search path or RPATH set.</p>	<p>None info</p> <p>The binary does not have RUNPATH set.</p>	<p>True info</p> <p>The binary has the following fortified functions: ['_strlen_chk']</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
92	arm64-v8a/libjsi.so	<p>True info</p> <p>The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>Dynamic Shared Object (DSO) info</p> <p>The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.</p>	<p>True info</p> <p>This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>None info</p> <p>The binary does not have run-time search path or RPATH set.</p>	<p>None info</p> <p>The binary does not have RUNPATH set.</p>	<p>True info</p> <p>The binary has the following fortified functions: ['_memcpy_chk', '_strlen_chk', '_memset_chk', '_vsnprintf_chk', '_fwrite_chk', '_write_chk', '_strncat_chk']</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
93	arm64-v8a/libstatic-webp.so	<p>True info</p> <p>The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>Dynamic Shared Object (DSO) info</p> <p>The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.</p>	<p>True info</p> <p>This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>None info</p> <p>The binary does not have run-time search path or RPATH set.</p>	<p>None info</p> <p>The binary does not have RUNPATH set.</p>	<p>True info</p> <p>The binary has the following fortified functions: ['_memcpy_chk']</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
94	arm64-v8a/libreanimated.so	<p>True info</p> <p>The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>Dynamic Shared Object (DSO) info</p> <p>The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.</p>	<p>True info</p> <p>This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>None info</p> <p>The binary does not have run-time search path or RPATH set.</p>	<p>None info</p> <p>The binary does not have RUNPATH set.</p>	<p>True info</p> <p>The binary has the following fortified functions: ['_strlen_chk']</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
95	arm64-v8a/libentry-android.so	<p>True info</p> <p>The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>Dynamic Shared Object (DSO) info</p> <p>The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.</p>	<p>True info</p> <p>This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>None info</p> <p>The binary does not have run-time search path or RPATH set.</p>	<p>None info</p> <p>The binary does not have RUNPATH set.</p>	<p>True info</p> <p>The binary has the following fortified functions: ['_vsnprintf_chk']</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
96	x86_64/libreactnative.so	<p>True info</p> <p>The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>Dynamic Shared Object (DSO) info</p> <p>The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.</p>	<p>True info</p> <p>This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>None info</p> <p>The binary does not have run-time search path or RPATH set.</p>	<p>None info</p> <p>The binary does not have RUNPATH set.</p>	<p>True info</p> <p>The binary has the following fortified functions: ['_strlen_chk', '_memcpy_chk', '_vsprintf_chk', '_memset_chk', '_fwrite_chk', '_write_chk', '_strncat_chk']</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
97	x86_64/libhermestooling.so	<p>True info</p> <p>The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>Dynamic Shared Object (DSO) info</p> <p>The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.</p>	<p>True info</p> <p>This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>None info</p> <p>The binary does not have run-time search path or RPATH set.</p>	<p>None info</p> <p>The binary does not have RUNPATH set.</p>	<p>True info</p> <p>The binary has the following fortified functions: ['_strlen_chk']</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
98	x86_64/libavif_android.so	<p>True info</p> <p>The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>Dynamic Shared Object (DSO) info</p> <p>The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.</p>	<p>True info</p> <p>This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>None info</p> <p>The binary does not have run-time search path or RPATH set.</p>	<p>None info</p> <p>The binary does not have RUNPATH set.</p>	<p>False warning</p> <p>The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
99	x86_64/libnative-imagetranscoder.so	<p>True info</p> <p>The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>Dynamic Shared Object (DSO) info</p> <p>The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.</p>	<p>True info</p> <p>This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>None info</p> <p>The binary does not have run-time search path or RPATH set.</p>	<p>None info</p> <p>The binary does not have RUNPATH set.</p>	<p>True info</p> <p>The binary has the following fortified functions: ['_vsprintf_chk', '_strlen_chk']</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
100	x86_64/libfbjni.so	<p>True info</p> <p>The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>Dynamic Shared Object (DSO) info</p> <p>The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.</p>	<p>True info</p> <p>This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>None info</p> <p>The binary does not have run-time search path or RPATH set.</p>	<p>None info</p> <p>The binary does not have RUNPATH set.</p>	<p>False warning</p> <p>The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
101	x86_64/libc++_shared.so	<p>True info</p> <p>The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>Dynamic Shared Object (DSO) info</p> <p>The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.</p>	<p>False high</p> <p>This binary does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option -fstack-protector-all to enable stack canaries. Not applicable for Dart/Flutter libraries unless Dart FFI is used.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>None info</p> <p>The binary does not have run-time search path or RPATH set.</p>	<p>None info</p> <p>The binary does not have RUNPATH set.</p>	<p>False warning</p> <p>The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
102	x86_64/libhermes.so	<p>True info</p> <p>The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>Dynamic Shared Object (DSO) info</p> <p>The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.</p>	<p>True info</p> <p>This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>None info</p> <p>The binary does not have run-time search path or RPATH set.</p>	<p>None info</p> <p>The binary does not have RUNPATH set.</p>	<p>True info</p> <p>The binary has the following fortified functions: ['_write_chk', '_strlen_chk', '_vsprintf_chk', '_strchr_chk']</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
103	x86_64/libnative-filters.so	<p>True info</p> <p>The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>Dynamic Shared Object (DSO) info</p> <p>The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.</p>	<p>True info</p> <p>This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>None info</p> <p>The binary does not have run-time search path or RPATH set.</p>	<p>None info</p> <p>The binary does not have RUNPATH set.</p>	<p>False warning</p> <p>The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
104	x86_64/libanimation-decoder-gif.so	<p>True info</p> <p>The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>Dynamic Shared Object (DSO) info</p> <p>The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.</p>	<p>True info</p> <p>This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>None info</p> <p>The binary does not have run-time search path or RPATH set.</p>	<p>None info</p> <p>The binary does not have RUNPATH set.</p>	<p>False warning</p> <p>The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
105	x86_64/librnscreens.so	<p>True info</p> <p>The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>Dynamic Shared Object (DSO) info</p> <p>The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.</p>	<p>True info</p> <p>This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>None info</p> <p>The binary does not have run-time search path or RPATH set.</p>	<p>None info</p> <p>The binary does not have RUNPATH set.</p>	<p>False warning</p> <p>The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
106	x86_64/libentry.so	<p>True info</p> <p>The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>Dynamic Shared Object (DSO) info</p> <p>The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.</p>	<p>True info</p> <p>This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>None info</p> <p>The binary does not have run-time search path or RPATH set.</p>	<p>None info</p> <p>The binary does not have RUNPATH set.</p>	<p>True info</p> <p>The binary has the following fortified functions: ['_vsprintf_chk', '__read_chk', '__memmove_chk', '__strncpy_chk', '__strlen_chk', '__memcpy_chk']</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
107	x86_64/libexpo-modules-core.so	<p>True info</p> <p>The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>Dynamic Shared Object (DSO) info</p> <p>The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.</p>	<p>True info</p> <p>This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>None info</p> <p>The binary does not have run-time search path or RPATH set.</p>	<p>None info</p> <p>The binary does not have RUNPATH set.</p>	<p>True info</p> <p>The binary has the following fortified functions: ['_strlen_chk']</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
108	x86_64/libgifimage.so	<p>True info</p> <p>The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>Dynamic Shared Object (DSO) info</p> <p>The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.</p>	<p>True info</p> <p>This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>None info</p> <p>The binary does not have run-time search path or RPATH set.</p>	<p>None info</p> <p>The binary does not have RUNPATH set.</p>	<p>False warning</p> <p>The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
109	x86_64/libimagepipeline.so	<p>True info</p> <p>The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>Dynamic Shared Object (DSO) info</p> <p>The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.</p>	<p>True info</p> <p>This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>None info</p> <p>The binary does not have run-time search path or RPATH set.</p>	<p>None info</p> <p>The binary does not have RUNPATH set.</p>	<p>False warning</p> <p>The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
110	x86_64/libworklets.so	<p>True info</p> <p>The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>Dynamic Shared Object (DSO) info</p> <p>The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.</p>	<p>True info</p> <p>This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>None info</p> <p>The binary does not have run-time search path or RPATH set.</p>	<p>None info</p> <p>The binary does not have RUNPATH set.</p>	<p>True info</p> <p>The binary has the following fortified functions: ['_strlen_chk']</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
111	x86_64/libjsi.so	<p>True info</p> <p>The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>Dynamic Shared Object (DSO) info</p> <p>The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.</p>	<p>True info</p> <p>This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>None info</p> <p>The binary does not have run-time search path or RPATH set.</p>	<p>None info</p> <p>The binary does not have RUNPATH set.</p>	<p>True info</p> <p>The binary has the following fortified functions: ['_memcpy_chk', '_strlen_chk', '_memset_chk', '_vsnprintf_chk', '_fwrite_chk', '_write_chk', '_strncat_chk']</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
112	x86_64/libstatic-webp.so	<p>True info</p> <p>The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>Dynamic Shared Object (DSO) info</p> <p>The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.</p>	<p>True info</p> <p>This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>None info</p> <p>The binary does not have run-time search path or RPATH set.</p>	<p>None info</p> <p>The binary does not have RUNPATH set.</p>	<p>True info</p> <p>The binary has the following fortified functions: ['_memcpy_chk']</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
113	x86_64/libreanimated.so	<p>True info</p> <p>The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>Dynamic Shared Object (DSO) info</p> <p>The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.</p>	<p>True info</p> <p>This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>None info</p> <p>The binary does not have run-time search path or RPATH set.</p>	<p>None info</p> <p>The binary does not have RUNPATH set.</p>	<p>True info</p> <p>The binary has the following fortified functions: ['_strlen_chk']</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
114	x86_64/lib Sentry-android.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['_vsnprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
115	armeabi-v7a/libreactnative.so	<p>True info</p> <p>The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>Dynamic Shared Object (DSO) info</p> <p>The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.</p>	<p>True info</p> <p>This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>None info</p> <p>The binary does not have run-time search path or RPATH set.</p>	<p>None info</p> <p>The binary does not have RUNPATH set.</p>	<p>True info</p> <p>The binary has the following fortified functions: ['_strlen_chk', '_memcpy_chk', '_vsprintf_chk', '_memset_chk', '_fwrite_chk', '_write_chk', '_strncat_chk']</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
116	armeabi-v7a/libhermestooling.so	<p>True info</p> <p>The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>Dynamic Shared Object (DSO) info</p> <p>The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.</p>	<p>True info</p> <p>This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>None info</p> <p>The binary does not have run-time search path or RPATH set.</p>	<p>None info</p> <p>The binary does not have RUNPATH set.</p>	<p>True info</p> <p>The binary has the following fortified functions: ['_strlen_chk']</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
117	armeabi-v7a/libavif_android.so	<p>True info</p> <p>The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>Dynamic Shared Object (DSO) info</p> <p>The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.</p>	<p>True info</p> <p>This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>None info</p> <p>The binary does not have run-time search path or RPATH set.</p>	<p>None info</p> <p>The binary does not have RUNPATH set.</p>	<p>False warning</p> <p>The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
118	armeabi-v7a/libnative-imagetranscoder.so	<p>True info</p> <p>The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>Dynamic Shared Object (DSO) info</p> <p>The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.</p>	<p>True info</p> <p>This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>None info</p> <p>The binary does not have run-time search path or RPATH set.</p>	<p>None info</p> <p>The binary does not have RUNPATH set.</p>	<p>True info</p> <p>The binary has the following fortified functions: ['_vsprintf_chk', '__strlen_chk', '__memcpy_chk']</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
119	armeabi-v7a/libfbjni.so	<p>True info</p> <p>The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>Dynamic Shared Object (DSO) info</p> <p>The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.</p>	<p>True info</p> <p>This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>None info</p> <p>The binary does not have run-time search path or RPATH set.</p>	<p>None info</p> <p>The binary does not have RUNPATH set.</p>	<p>False warning</p> <p>The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
120	armeabi-v7a/libc++_shared.so	<p>True info</p> <p>The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>Dynamic Shared Object (DSO) info</p> <p>The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.</p>	<p>False high</p> <p>This binary does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option -fstack-protector-all to enable stack canaries. Not applicable for Dart/Flutter libraries unless Dart FFI is used.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>None info</p> <p>The binary does not have run-time search path or RPATH set.</p>	<p>None info</p> <p>The binary does not have RUNPATH set.</p>	<p>False warning</p> <p>The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
121	armeabi-v7a/libhermes.so	<p>True info</p> <p>The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>Dynamic Shared Object (DSO) info</p> <p>The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.</p>	<p>True info</p> <p>This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>None info</p> <p>The binary does not have run-time search path or RPATH set.</p>	<p>None info</p> <p>The binary does not have RUNPATH set.</p>	<p>True info</p> <p>The binary has the following fortified functions: ['_write_chk', '_strlen_chk', '_vsprintf_chk', '_strchr_chk']</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
122	armeabi-v7a/libnative-filters.so	<p>True info</p> <p>The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>Dynamic Shared Object (DSO) info</p> <p>The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.</p>	<p>True info</p> <p>This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>None info</p> <p>The binary does not have run-time search path or RPATH set.</p>	<p>None info</p> <p>The binary does not have RUNPATH set.</p>	<p>False warning</p> <p>The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
123	armeabi-v7a/libanimation-decoder-gif.so	<p>True info</p> <p>The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>Dynamic Shared Object (DSO) info</p> <p>The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.</p>	<p>True info</p> <p>This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>None info</p> <p>The binary does not have run-time search path or RPATH set.</p>	<p>None info</p> <p>The binary does not have RUNPATH set.</p>	<p>False warning</p> <p>The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
124	armeabi-v7a/librnscreens.so	<p>True info</p> <p>The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>Dynamic Shared Object (DSO) info</p> <p>The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.</p>	<p>True info</p> <p>This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>None info</p> <p>The binary does not have run-time search path or RPATH set.</p>	<p>None info</p> <p>The binary does not have RUNPATH set.</p>	<p>False warning</p> <p>The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
125	armeabi-v7a/lib Sentry.so	<p>True info</p> <p>The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>Dynamic Shared Object (DSO) info</p> <p>The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.</p>	<p>True info</p> <p>This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>None info</p> <p>The binary does not have run-time search path or RPATH set.</p>	<p>None info</p> <p>The binary does not have RUNPATH set.</p>	<p>True info</p> <p>The binary has the following fortified functions: ['_vsnprintf_chk', '__read_chk', '__memmove_chk', '__strncpy_chk', '__strlen_chk', '__memcpy_chk']</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
126	armeabi-v7a/libexpo-modules-core.so	<p>True info</p> <p>The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>Dynamic Shared Object (DSO) info</p> <p>The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.</p>	<p>True info</p> <p>This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>None info</p> <p>The binary does not have run-time search path or RPATH set.</p>	<p>None info</p> <p>The binary does not have RUNPATH set.</p>	<p>True info</p> <p>The binary has the following fortified functions: ['_strlen_chk', '_vsprintf_chk']</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
127	armeabi-v7a/libgifimage.so	<p>True info</p> <p>The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>Dynamic Shared Object (DSO) info</p> <p>The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.</p>	<p>True info</p> <p>This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>None info</p> <p>The binary does not have run-time search path or RPATH set.</p>	<p>None info</p> <p>The binary does not have RUNPATH set.</p>	<p>True info</p> <p>The binary has the following fortified functions: ['_vsnprintf_chk']</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
128	armeabi-v7a/libimagepipeline.so	<p>True info</p> <p>The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>Dynamic Shared Object (DSO) info</p> <p>The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.</p>	<p>True info</p> <p>This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>None info</p> <p>The binary does not have run-time search path or RPATH set.</p>	<p>None info</p> <p>The binary does not have RUNPATH set.</p>	<p>False warning</p> <p>The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
129	armeabi-v7a/libworklets.so	<p>True info</p> <p>The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>Dynamic Shared Object (DSO) info</p> <p>The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.</p>	<p>True info</p> <p>This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>None info</p> <p>The binary does not have run-time search path or RPATH set.</p>	<p>None info</p> <p>The binary does not have RUNPATH set.</p>	<p>True info</p> <p>The binary has the following fortified functions: ['_strlen_chk']</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
130	armeabi-v7a/libjsi.so	<p>True info</p> <p>The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>Dynamic Shared Object (DSO) info</p> <p>The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.</p>	<p>True info</p> <p>This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>None info</p> <p>The binary does not have run-time search path or RPATH set.</p>	<p>None info</p> <p>The binary does not have RUNPATH set.</p>	<p>True info</p> <p>The binary has the following fortified functions: ['_memcpy_chk', '_strlen_chk', '_vsprintf_chk', '_memset_chk', '_fwrite_chk', '_write_chk', '_strncat_chk']</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
131	armeabi-v7a/libstatic-webp.so	<p>True info</p> <p>The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>Dynamic Shared Object (DSO) info</p> <p>The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.</p>	<p>True info</p> <p>This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>None info</p> <p>The binary does not have run-time search path or RPATH set.</p>	<p>None info</p> <p>The binary does not have RUNPATH set.</p>	<p>True info</p> <p>The binary has the following fortified functions: ['_vsprintf_chk', '_memcpy_chk']</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
132	armeabi-v7a/libreanimated.so	<p>True info</p> <p>The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>Dynamic Shared Object (DSO) info</p> <p>The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.</p>	<p>True info</p> <p>This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>None info</p> <p>The binary does not have run-time search path or RPATH set.</p>	<p>None info</p> <p>The binary does not have RUNPATH set.</p>	<p>True info</p> <p>The binary has the following fortified functions: ['_strlen_chk', '_vsprintf_chk']</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
133	armeabi-v7a/libentry-android.so	<p>True info</p> <p>The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>Dynamic Shared Object (DSO) info</p> <p>The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.</p>	<p>True info</p> <p>This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>None info</p> <p>The binary does not have run-time search path or RPATH set.</p>	<p>None info</p> <p>The binary does not have RUNPATH set.</p>	<p>True info</p> <p>The binary has the following fortified functions: ['_vsprintf_chk']</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
134	x86/libreactnative.so	<p>True info</p> <p>The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>Dynamic Shared Object (DSO) info</p> <p>The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.</p>	<p>True info</p> <p>This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>None info</p> <p>The binary does not have run-time search path or RPATH set.</p>	<p>None info</p> <p>The binary does not have RUNPATH set.</p>	<p>True info</p> <p>The binary has the following fortified functions: ['_strlen_chk', '_memcpy_chk', '_vsnprintf_chk', '_memset_chk', '_fwrite_chk', '_write_chk', '_strncat_chk']</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
135	x86/libhermestooling.so	<p>True info</p> <p>The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>Dynamic Shared Object (DSO) info</p> <p>The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.</p>	<p>True info</p> <p>This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>None info</p> <p>The binary does not have run-time search path or RPATH set.</p>	<p>None info</p> <p>The binary does not have RUNPATH set.</p>	<p>True info</p> <p>The binary has the following fortified functions: ['_strlen_chk']</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
136	x86/libavif_android.so	<p>True info</p> <p>The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>Dynamic Shared Object (DSO) info</p> <p>The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.</p>	<p>True info</p> <p>This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>None info</p> <p>The binary does not have run-time search path or RPATH set.</p>	<p>None info</p> <p>The binary does not have RUNPATH set.</p>	<p>False warning</p> <p>The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
137	x86/libnative-imagetranscoder.so	<p>True info</p> <p>The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>Dynamic Shared Object (DSO) info</p> <p>The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.</p>	<p>True info</p> <p>This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>None info</p> <p>The binary does not have run-time search path or RPATH set.</p>	<p>None info</p> <p>The binary does not have RUNPATH set.</p>	<p>True info</p> <p>The binary has the following fortified functions: ['_vsprintf_chk', '_strlen_chk']</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
138	x86/libfbjni.so	<p>True info</p> <p>The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>Dynamic Shared Object (DSO) info</p> <p>The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.</p>	<p>True info</p> <p>This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>None info</p> <p>The binary does not have run-time search path or RPATH set.</p>	<p>None info</p> <p>The binary does not have RUNPATH set.</p>	<p>False warning</p> <p>The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
139	x86/libc++_shared.so	<p>True info</p> <p>The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>Dynamic Shared Object (DSO) info</p> <p>The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.</p>	<p>False high</p> <p>This binary does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option -fstack-protector-all to enable stack canaries. Not applicable for Dart/Flutter libraries unless Dart FFI is used.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>None info</p> <p>The binary does not have run-time search path or RPATH set.</p>	<p>None info</p> <p>The binary does not have RUNPATH set.</p>	<p>False warning</p> <p>The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
140	x86/libhermes.so	<p>True info</p> <p>The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>Dynamic Shared Object (DSO) info</p> <p>The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.</p>	<p>True info</p> <p>This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>None info</p> <p>The binary does not have run-time search path or RPATH set.</p>	<p>None info</p> <p>The binary does not have RUNPATH set.</p>	<p>True info</p> <p>The binary has the following fortified functions: ['_write_chk', '_strlen_chk', '_vsprintf_chk', '_strchr_chk']</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
141	x86/libnative-filters.so	<p>True info</p> <p>The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>Dynamic Shared Object (DSO) info</p> <p>The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.</p>	<p>True info</p> <p>This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>None info</p> <p>The binary does not have run-time search path or RPATH set.</p>	<p>None info</p> <p>The binary does not have RUNPATH set.</p>	<p>False warning</p> <p>The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
142	x86/libanimation-decoder-gif.so	<p>True info</p> <p>The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>Dynamic Shared Object (DSO) info</p> <p>The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.</p>	<p>True info</p> <p>This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>None info</p> <p>The binary does not have run-time search path or RPATH set.</p>	<p>None info</p> <p>The binary does not have RUNPATH set.</p>	<p>False warning</p> <p>The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
143	x86/librnscreens.so	<p>True info</p> <p>The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>Dynamic Shared Object (DSO) info</p> <p>The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.</p>	<p>True info</p> <p>This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>None info</p> <p>The binary does not have run-time search path or RPATH set.</p>	<p>None info</p> <p>The binary does not have RUNPATH set.</p>	<p>False warning</p> <p>The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
144	x86/libsentry.so	<p>True info</p> <p>The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>Dynamic Shared Object (DSO) info</p> <p>The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.</p>	<p>True info</p> <p>This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>None info</p> <p>The binary does not have run-time search path or RPATH set.</p>	<p>None info</p> <p>The binary does not have RUNPATH set.</p>	<p>True info</p> <p>The binary has the following fortified functions: ['_vsnprintf_chk', '__read_chk', '__memmove_chk', '__strncpy_chk', '__strlen_chk', '__memcpy_chk']</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
145	x86/libexpo-modules-core.so	<p>True info</p> <p>The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>Dynamic Shared Object (DSO) info</p> <p>The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.</p>	<p>True info</p> <p>This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>None info</p> <p>The binary does not have run-time search path or RPATH set.</p>	<p>None info</p> <p>The binary does not have RUNPATH set.</p>	<p>True info</p> <p>The binary has the following fortified functions: ['_strlen_chk']</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
146	x86/libgifimage.so	<p>True info</p> <p>The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>Dynamic Shared Object (DSO) info</p> <p>The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.</p>	<p>True info</p> <p>This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>None info</p> <p>The binary does not have run-time search path or RPATH set.</p>	<p>None info</p> <p>The binary does not have RUNPATH set.</p>	<p>False warning</p> <p>The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
147	x86/libimagepipeline.so	<p>True info</p> <p>The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>Dynamic Shared Object (DSO) info</p> <p>The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.</p>	<p>True info</p> <p>This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>None info</p> <p>The binary does not have run-time search path or RPATH set.</p>	<p>None info</p> <p>The binary does not have RUNPATH set.</p>	<p>False warning</p> <p>The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
148	x86/libworklets.so	<p>True info</p> <p>The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>Dynamic Shared Object (DSO) info</p> <p>The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.</p>	<p>True info</p> <p>This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>None info</p> <p>The binary does not have run-time search path or RPATH set.</p>	<p>None info</p> <p>The binary does not have RUNPATH set.</p>	<p>True info</p> <p>The binary has the following fortified functions: ['_strlen_chk']</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
149	x86/libjsi.so	<p>True info</p> <p>The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>Dynamic Shared Object (DSO) info</p> <p>The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.</p>	<p>True info</p> <p>This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>None info</p> <p>The binary does not have run-time search path or RPATH set.</p>	<p>None info</p> <p>The binary does not have RUNPATH set.</p>	<p>True info</p> <p>The binary has the following fortified functions: ['_memcpy_chk', '_strlen_chk', '_memset_chk', '_vsnprintf_chk', '_fwrite_chk', '_write_chk', '_strncat_chk']</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
150	x86/libstatic-webp.so	<p>True info</p> <p>The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>Dynamic Shared Object (DSO) info</p> <p>The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.</p>	<p>True info</p> <p>This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>None info</p> <p>The binary does not have run-time search path or RPATH set.</p>	<p>None info</p> <p>The binary does not have RUNPATH set.</p>	<p>True info</p> <p>The binary has the following fortified functions: ['_memcpy_chk']</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
151	x86/libreanimated.so	<p>True info</p> <p>The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>Dynamic Shared Object (DSO) info</p> <p>The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.</p>	<p>True info</p> <p>This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>None info</p> <p>The binary does not have run-time search path or RPATH set.</p>	<p>None info</p> <p>The binary does not have RUNPATH set.</p>	<p>True info</p> <p>The binary has the following fortified functions: ['_strlen_chk']</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
152	x86/libsentry-android.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['_vsprintf_chk']	True info Symbols are stripped.

NIAP ANALYSIS v1.3

NO	IDENTIFIER	REQUIREMENT	FEATURE	DESCRIPTION
----	------------	-------------	---------	-------------



BEHAVIOUR ANALYSIS

RULE ID	BEHAVIOUR	LABEL	FILES
00191	Get messages in the SMS inbox	sms	expo/modules/medialibrary/assets/AssetUtilsKt.java me/leolin/shortcutbadger/impl/SamsungHomeBadger.java
00022	Open a file from given absolute path of the file	file	coil3/util/FileSystems_androidKt.java expo/modules/audio/AudioRecorder.java expo/modules/filesystem/legacy/FileSystemLegacyModule.java expo/modules/font/FontUtilsModule.java expo/modules/image/ExpolImageModule.java expo/modules/imagepicker/exporters/DimensionsExporter.java expo/modules/medialibrary/next/objects/album/Album.java expo/modules/updates/UpdatesUtils.java io/sentry/DirectoryProcessor.java io/sentry/EnvelopeSender.java io/sentry/OutboxSender.java io/sentry/PreviousSessionFinalizer.java io/sentry/SentryOptions.java io/sentry/android/core/AndroidOptionsInitializer.java io/sentry/android/core/DeviceInfoUtil.java io/sentry/android/core/cache/AndroidEnvelopeCache.java io/sentry/android/replay/ReplayCache.java io/sentry/android/replay/capture/BufferCaptureStrategy.java io/sentry/cache/CacheStrategy.java io/sentry/cache/CacheUtils.java io/sentry/cache/EnvelopeCache.java io/sentry/instrumentation/file/FileIOSpanManager.java io/sentry/react/RNSentryModuleImpl.java
00089	Connect to a URL and receive input stream from the server	command network	com/bumptech/glide/load/data/HttpUrlFetcher.java expo/modules/updates/reloadscreen/ReloadScreenView\$loadImageFromUrl\$1.java io/sentry/transport/HttpConnection.java

RULE ID	BEHAVIOUR	LABEL	FILES
00030	Connect to the remote server through the given URL	network	com/bumptech/glide/load/data/HttpUrlFetcher.java expo/modules/updates/reloadscreen/ReloadScreenView\$loadImageFromUrl\$1.java io/sentry/transport/HttpConnection.java

RULE ID	BEHAVIOUR	LABEL	FILES
00013	Read file and put it into a stream	file	com/bumptech/glide/disklruCache/DiskLruCache.java com/bumptech/glide/load/ImageHeaderParserUtils.java com/bumptech/glide/load/model/FileLoader.java com/bumptech/glide/load/resource/bitmap/ImageReader.java com/canhub/cropper/Utils/GetUriForFileKt.java com/github/penfeizhou/animation/apng/decode/APNGParser.java com/github/penfeizhou/animation/avif/decode/AVIFParser.java com/github/penfeizhou/animation/gif/decode/GifParser.java com/github/penfeizhou/animation/io/FileReader.java com/github/penfeizhou/animation/webp/decode/WebPParser.java com/reactnativecommunity/asyncstorage/AsyncStorageExpoMigration.java com/rnmaps/maps/FileUtil.java com/rnmaps/maps/MapLocalTile.java com/rnmaps/maps/MapTileProvider.java expo/modules/asset/FileUtilsKt.java expo/modules/core/logging/PersistentFileLog.java expo/modules/filesystem/legacy/FileSystemLegacyModule.java expo/modules/filesystem/unifiedfile/JavaFile.java expo/modules/medialibrary/MediaLibraryUtils.java expo/modules/medialibrary/assets/CreateAssetWithAlbumFile\$writeFileContentsToAsset\$2.java expo/modules/medialibrary/next/extensions/FileExtensionsKt.java expo/modules/updates/UpdatesUtils.java io/sentry/EnvelopeSender.java io/sentry/OutboxSender.java io/sentry/PreviousSessionFinalizer.java io/sentry/android/core/SentryPerformanceProvider.java io/sentry/android/replay/ReplayCache.java io/sentry/cache/CacheStrategy.java io/sentry/cache/CacheUtils.java io/sentry/cache/EnvelopeCache.java io/sentry/config/FileSystemPropertiesLoader.java io/sentry/instrumentation/file/FileInputStreamInitData.java io/sentry/instrumentation/file/SentryFileInputStream.java io/sentry/util/FileUtils.java okio/Okio__JvmOkioKt.java

RULE ID	BEHAVIOUR	LABEL	FILES
00036	Get resource file from res/raw directory	reflection	com/canhub/cropper/Utils/GetUriForFileKt.java com/rnmaps/maps/ImageReader.java com/rnmaps/maps/MapMarker.java expo/modules/adapters/react/permissions/PermissionsService.java expo/modules/asset/ResourceAssetKt.java expo/modules/audio/AudioModule.java expo/modules/filesystem/legacy/FileSystemLegacyModule.java expo/modules/image/records/SourceMap.java expo/modules/notifications/notifications/model/NotificationContent.java expo/modules/notifications/service/NotificationsService.java expo/modules/updates/UpdatesConfiguration.java expo/modules/updates/Utils/AndroidResourceAssetUtils.java io/sentry/react/RNSentryModuleImpl.java me/leolin/shortcutbadger/impl/EverythingMeHomeBadger.java me/leolin/shortcutbadger/impl/HuaweiHomeBadger.java me/leolin/shortcutbadger/impl/NovaHomeBadger.java me/leolin/shortcutbadger/impl/OPPOHomeBader.java me/leolin/shortcutbadger/impl/SamsungHomeBadger.java me/leolin/shortcutbadger/impl/SonyHomeBadger.java
00009	Put data in cursor to JSON object	file	com/reactnativecommunity/asyncstorage/AsyncLocalStorageUtil.java
00091	Retrieve data from broadcast	collection	expo/modules/location/services/LocationTaskService.java expo/modules/notifications/service/NotificationsService.java
00189	Get the content of a SMS message	sms	expo/modules/imagepicker/ImagePickerUtilsKt.java expo/modules/imagepicker/MediaHandler.java expo/modules/medialibrary/MediaLibraryUtils.java me/leolin/shortcutbadger/impl/SamsungHomeBadger.java
00188	Get the address of a SMS message	sms	expo/modules/imagepicker/ImagePickerUtilsKt.java expo/modules/imagepicker/MediaHandler.java expo/modules/medialibrary/MediaLibraryUtils.java me/leolin/shortcutbadger/impl/SamsungHomeBadger.java
00011	Query data from URI (SMS, CALLLOGS)	sms calllog collection	me/leolin/shortcutbadger/impl/SamsungHomeBadger.java

RULE ID	BEHAVIOUR	LABEL	FILES
00200	Query data from the contact list	collection contact	expo/modules/imagepicker/ImagePickerUtilsKt.java expo/modules/imagepicker/MediaHandler.java expo/modules/medialibrary/MediaLibraryUtils.java me/leolin/shortcutbadger/impl/SamsungHomeBadger.java
00187	Query a URI and check the result	collection sms calllog calendar	expo/modules/medialibrary/MediaLibraryUtils.java me/leolin/shortcutbadger/impl/SamsungHomeBadger.java
00201	Query data from the call log	collection calllog	expo/modules/imagepicker/ImagePickerUtilsKt.java expo/modules/imagepicker/MediaHandler.java expo/modules/medialibrary/MediaLibraryUtils.java me/leolin/shortcutbadger/impl/SamsungHomeBadger.java
00077	Read sensitive data(SMS, CALLLOG, etc)	collection sms calllog calendar	com/bumptech/glide/load/data/mediastore/ThumbFetcher.java expo/modules/imagepicker/MediaHandler.java expo/modules/medialibrary/MediaLibraryModule.java expo/modules/medialibrary/MediaLibraryUtils.java expo/modules/medialibrary/assets/AssetUtilsKt\$queryAssetInfo\$2.java expo/modules/medialibrary/assets/GetAssetsKt.java me/leolin/shortcutbadger/impl/SamsungHomeBadger.java
00014	Read file into a stream and put it into a JSON object	file	expo/modules/updates/UpdatesUtils.java
00005	Get absolute path of file and put it to JSON object	file	expo/modules/updates/UpdatesUtils.java

RULE ID	BEHAVIOUR	LABEL	FILES
00063	Implicit intent(view a web page, make a phone call, etc.)	control	expo/modules/adapters/react/permissions/PermissionsService.java expo/modules/filesystem/legacy/FileSystemLegacyModule.java expo/modules/imagepicker/contracts/CameraContract.java expo/modules/imagepicker/contracts/CropImageContract.java expo/modules/notifications/service/NotificationsService.java expo/modules/sharing/SharingModule.java expo/modules/webbrowser/CustomTabsActivitiesHelperKt.java me/leolin/shortcutbadger/impl/OPPOHomeBader.java me/leolin/shortcutbadger/impl/SonyHomeBadger.java
00001	Initialize bitmap object and compress data (e.g. JPEG) into bitmap object	camera	com/rnmaps/maps/ImageUtil.java com/rnmaps/maps/MapTileProvider.java expo/modules/clipboard/ClipboardImageKt.java
00096	Connect to a URL and set request method	command network	io/sentry/transport/HttpConnection.java
00109	Connect to a URL and get the response code	network command	com/bumptech/glide/load/data/HttpUrlFetcher.java io/sentry/transport/HttpConnection.java
00012	Read data and put it into a buffer stream	file	io/sentry/EnvelopeSender.java io/sentry/OutboxSender.java io/sentry/cache/CacheStrategy.java io/sentry/cache/EnvelopeCache.java io/sentry/config/FileSystemPropertiesLoader.java io/sentry/util/FileUtils.java
00121	Create a directory	file command	expo/modules/filesystem/legacy/FileSystemLegacyModule.java expo/modules/medialibrary/albums/AlbumUtilsKt.java
00024	Write file after Base64 decoding	reflection file	expo/modules/filesystem/legacy/FileSystemLegacyModule.java
00125	Check if the given file path exist	file	expo/modules/filesystem/legacy/FileSystemLegacyModule.java expo/modules/medialibrary/albums/AlbumUtilsKt.java

RULE ID	BEHAVIOUR	LABEL	FILES
00104	Check if the given path is directory	file	expo/modules/filesystem/legacy/FileSystemLegacyModule.java
00028	Read file from assets directory	file	com/caverock/androidsvg/SimpleAssetResolver.java
00147	Get the time of current location	collection location	expo/modules/location/LocationHelpers.java
00051	Implicit intent(view a web page, make a phone call, etc.) via setData	control	expo/modules/adapters/react/permissions/PermissionsService.java expo/modules/webbrowser/CustomTabsActivitiesHelperKt.java
00195	Set the output path of the recorded file	record file	expo/modules/audio/AudioRecorder.java
00199	Stop recording and release recording resources	record	expo/modules/audio/AudioRecorder.java
00198	Initialize the recorder and start recording	record	expo/modules/audio/AudioRecorder.java
00194	Set the audio source (MIC) and recorded file format	record	expo/modules/audio/AudioRecorder.java
00197	Set the audio encoder and initialize the recorder	record	expo/modules/audio/AudioRecorder.java
00007	Use absolute path of directory for the output media file path	file	expo/modules/audio/AudioRecorder.java
00196	Set the recorded file format and output path	record file	expo/modules/audio/AudioRecorder.java
00041	Save recorded audio/video to file	record	expo/modules/audio/AudioRecorder.java
00175	Get notification manager and cancel notifications	notification	expo/modules/notifications/badge/BadgeHelper.java expo/modules/notifications/service/delegates/ExpoPresentationDelegate.java

RULE ID	BEHAVIOUR	LABEL	FILES
00075	Get location of the device	collection location	expo/modules/location/LocationModule.java
00115	Get last known location of the device	collection location	expo/modules/location/LocationModule.java

FIREBASE DATABASES ANALYSIS

TITLE	SEVERITY	DESCRIPTION
Firebase Remote Config disabled	secure	Firebase Remote Config is disabled for https://firebase-remoteconfig.googleapis.com/v1/projects/552326752490/namespaces/firebase:fetch?key=AlzaSyAilMq_wRPt94_dxxWlrm3ljbmNv4HvQ_s . This is indicated by the response: {'state': 'NO_TEMPLATE'}

ABUSED PERMISSIONS

TYPE	MATCHES	PERMISSIONS
Malware Permissions	8/25	android.permission.ACCESS_COARSE_LOCATION, android.permission.ACCESS_FINE_LOCATION, android.permission.INTERNET, android.permission.RECORD_AUDIO, android.permission.VIBRATE, android.permission.ACCESS_NETWORK_STATE, android.permission.WAKE_LOCK, android.permission.CAMERA
Other Common Permissions	3/44	android.permission.MODIFY_AUDIO_SETTINGS, com.google.android.c2dm.permission.RECEIVE, com.google.android.finsky.permission.BIND_GET_INSTALL_REFERRER_SERVICE

Malware Permissions:

Top permissions that are widely abused by known malware.

Other Common Permissions:

Permissions that are commonly abused by known malware.

! OFAC SANCTIONED COUNTRIES

This app may communicate with the following OFAC sanctioned list of countries.

DOMAIN	COUNTRY/REGION
--------	----------------

🔍 DOMAIN MALWARE CHECK

DOMAIN	STATUS	GEOLOCATION
www.icon	ok	No Geolocation information available.
www.interpretation	ok	No Geolocation information available.
expo.dev	ok	IP: 104.18.4.104 Country: United States of America Region: California City: San Francisco Latitude: 37.775700 Longitude: -122.395203 View: Google Map
docs.expo.dev	ok	IP: 104.18.5.104 Country: United States of America Region: California City: San Francisco Latitude: 37.775700 Longitude: -122.395203 View: Google Map
www.language	ok	No Geolocation information available.

DOMAIN	STATUS	GEOLOCATION
.jpg	ok	No Geolocation information available.
www.wencodeuricomponent	ok	No Geolocation information available.
www.googleorganizationautocomplete requirementsconservative	ok	No Geolocation information available.
expo.fyi	ok	IP: 216.150.1.1 Country: Canada Region: Ontario City: Etobicoke Latitude: 43.623768 Longitude: -79.559723 View: Google Map
www.world	ok	IP: 75.2.38.108 Country: United States of America Region: Washington City: Seattle Latitude: 47.606209 Longitude: -122.332069 View: Google Map
.css	ok	No Geolocation information available.
docs.swmansion.com	ok	IP: 104.26.9.117 Country: United States of America Region: California City: San Francisco Latitude: 37.775700 Longitude: -122.395203 View: Google Map
www.in	ok	No Geolocation information available.

DOMAIN	STATUS	GEOLOCATION
10.0.2.2	ok	IP: 10.0.2.2 Country: - Region: - City: - Latitude: 0.000000 Longitude: 0.000000 View: Google Map
www.text-decoration	ok	No Geolocation information available.
www.recent	ok	No Geolocation information available.
xml.org	ok	IP: 172.67.205.113 Country: United States of America Region: California City: San Francisco Latitude: 37.775700 Longitude: -122.395203 View: Google Map
filesystem.local	ok	No Geolocation information available.
reactnative.dev	ok	IP: 63.176.8.218 Country: United States of America Region: Virginia City: Reston Latitude: 38.925961 Longitude: -77.397331 View: Google Map

DOMAIN	STATUS	GEOLOCATION
github.com	ok	IP: 140.82.121.4 Country: United States of America Region: California City: San Francisco Latitude: 37.775700 Longitude: -122.395203 View: Google Map
www.css	ok	No Geolocation information available.
docs.sentry.io	ok	IP: 66.33.60.193 Country: Canada Region: Ontario City: Etobicoke Latitude: 43.623768 Longitude: -79.559723 View: Google Map
www.risktabsprev10pxrise25pxblueding300ballfordearnwildbox.fairlackverspairjunetechifpickevil	ok	No Geolocation information available.
xmlpull.org	ok	IP: 185.199.108.153 Country: United States of America Region: Pennsylvania City: California Latitude: 40.065632 Longitude: -79.891708 View: Google Map
www.w3.org	ok	IP: 104.18.22.19 Country: United States of America Region: California City: San Francisco Latitude: 37.775700 Longitude: -122.395203 View: Google Map

DOMAIN	STATUS	GEOLOCATION
www.years	ok	No Geolocation information available.
www.c	ok	No Geolocation information available.
www.a	ok	No Geolocation information available.
www.style	ok	IP: 75.2.38.108 Country: United States of America Region: Washington City: Seattle Latitude: 47.606209 Longitude: -122.332069 View: Google Map
www.manifestations	ok	No Geolocation information available.
www.hortcut	ok	No Geolocation information available.

EMAILS

EMAIL	FILE
your.email@example.org	io/sentry/SentryFeedbackOptions.java

TRACKERS

TRACKER	CATEGORIES	URL
Sentry	Crash reporting	https://reports.exodus-privacy.eu.org/trackers/447

HARDCODED SECRETS

POSSIBLE SECRETS
"google_crash_reporting_api_key" : "AlzaSyAiIMq_wRPt94_dxxWlrn3ljbmNv4HvQ_s"
"google_api_key" : "AlzaSyAiIMq_wRPt94_dxxWlrn3ljbmNv4HvQ_s"
D2C0FB15760860DEF1EEF4D696E6768756151754
6A91174076B1E0E19C39C031FE8685C1CAE040E5C69A28EF
D35E472036BC4FB7E13C785ED201E065F98FCFA6F6F40DEF4F92B9EC7893EC28FCD412B1F1B32E24
b5440ed496eaba333f58c3ce160f54f8
C302F41D932A36CDA7A3463093D18DB78FCE476DE1A86294
0667ACEB38AF4E488C407433FFAE4F1C811638DF20
DC9203E514A721875485A529D2C722FB187BC8980EB866644DE41C68E143064546E861C0E2C9EDD92ADE71F46FCF50FF2AD97F951FDA9F2A2EB6546F39689BD3
8138e8a0fcf3a4e84a771d40fd305d7f4aa59306d7251de54d98af8fe95729a1f73d893fa424cd2edc8636a6c3285e022b0e3866a565ae8108eed8591cd4fe8d2ce86165a978d719ebf647f362d33fca29cd179fb42401cbaf3df0c614056f9c8f3cfd51e474afb6bc6974f78db8aba8e9e517fded658591ab7502bd41849462f
216EE8B189D291A0224984C1E92F1D16BF75CCD825A087A239B276D3167743C52C02D6E7232AA
1b9fa3e518d683c6b65763694ac8efbaec6fab44f2276171a42726507dd08add4c3b3f4c1ebc5b1222ddba077f722943b24c3edfa0f85fe24d0c8c01591f0be6f63

POSSIBLE SECRETS

4B337D934104CD7BEF271BF60CED1ED20DA14C08B3BB64F18A60888D

043B4C382CE37AA192A4019E763036F4F5DD4D7EBB938CF935318FDCE6BC28286531733C3F03C4FEE

255705fa2a306654b1f4cb03d6a750a30c250102d4988717d9ba15ab6d3e

0418DE98B02DB9A306F2AFCD7235F72A819B80AB12EBD65317247FECD462AABFFC4FF191B946A5F54D8D0AA2F418808CC25AB056962D30651A114AFD2755AD336747F93475
B7A1FCA3B88F2B6A208CCFE469408584DC2B2912675BF5B9E582928

4fe342e2fe1a7f9b8ee7eb4a7c0f9e162bce33576b315ececbb6406837bf51f5

D7C134AA264366862A18302575D1D787B09F075797DA89F57EC8C0FC

ffffffff00000000ffffffffffffbce6faada7179e84f3b9cac2fc632551

71FE1AF926CF847989EFEF8DB459F66394D90F32AD3F15E8

048BD2AEB9CB7E57CB2C4B482FFC81B7AFB9DE27E1E3BD23C23A4453BD9ACE3262547EF835C3DAC4FD97F8461A14611DC9C27745132DED8E545C1D54C72F046997

7A1F6653786A68192803910A3D30B2A2018B21CD54

e43bb460f0b80cc0c0b075798e948060f8321b7d

9B9F605F5A858107AB1EC85E6B41C8AACF846E86789051D37998F7B9022D759B

D6031998D1B3BBFEBF59CC9BBFF9AEE1

POSSIBLE SECRETS

FFFFFFFFFFFFFFFFC90FDAA22168C234C4C6628B80DC1CD129024E088A67CC74020BBEA63B139B22514A08798E3404DDEF9519B3CD3A431B302B0A6DF25F14374FE1356D6D51C245E485B576625E7EC6F44C42E9A637ED6B0BFF5CB6F406B7EDEE386BFB5A899FA5AE9F24117C4B1FE649286651ECE45B3DC2007CB8A163BF0598DA48361C55D39A69163FA8FD24CF5F83655D23DCA3AD961C62F356208552BB9ED529077096966D670C354E4ABC9804F1746C08CA18217C32905E462E36CE3BE39E772C180E86039B2783A2EC07A28FB5C55DF06F4C52C9DE2BCBF6955817183995497CEA956AE515D2261898FA051015728E5A8AAAC42DAD33170D04507A33A85521ABDF1CBA64ECFB850458DBEF0A8AEA71575D060C7DB3970F85A6E1E4C7ABF5AE8CDB0933D71E8C94E04A25619DCEE3D2261AD2EE6BF12FFA06D98A0864D87602733EC86A64521F2B18177B200CBBE117577A615D6C770988C0BAD946E208E24FA074E5AB3143DB5BFCE0FD108E4B82D120A92108011A723C12A787E6D788719A10BDBA5B2699C327186AF4E23C1A946834B6150BDA2583E9CA2AD44CE8DBBBC2DB04DE8EF92E8EFC141FBCEAA6287C59474E6BC05D99B2964FA090C3A2233BA186515BE7ED1F612970CEE2D7AFB81BDD762170481CD0069127D5B05AA993B4EA988D8FDDC186FFB7DC90A6C08F4DF435C934063199FFFFFFFFFFFFFFF

10C0FB15760860DEF1EEF4D696E676875615175D

04161FF7528B899B2D0C28607CA52C5B86CF5AC8395BAFEB13C02DA292DDED7A83

10686D41FF744D4449FCCF6D8EEA03102E6812C93A9D60B978B702CF156D814EF

044AD5F7048DE709AD51236DE65E4D4B482C836DC6E410664002BB3A02D4AAADACAE24817A4CA3A1B014B5270432DB27D2

91A091F03B5FBA4AB2CCF49C4EDD220FB028712D42BE752B2C40094DBACDB586FB20

8CB91E82A3386D280F5D6F7E50E641DF152F7109ED5456B31F166E6CAC0425A7CF3AB6AF6B7FC3103B883202E9046565

FD0D693149A118F651E6DCE6802085377E5F882D1B510B44160074C1288078365A0396C8E681

D35E472036BC4FB7E13C785ED201E065F98FCA5B68F12A32D482EC7EE8658E98691555B44C59311

01AF286BCA1AF286BCA1AF286BCA1AF286BCA1AF286BC9FB8F6B85C556892C20A7EB964FE7719E74F490758D3B

9760508f15230bccb292b982a2eb840bf0581cf5

6b016c3bdcf18941d0d654921475ca71a9db2fb27d1d37796185c2942c0a

2AA058F73A0E33AB486B0F610410C53A7F132310

3826F008A8C51D7B95284D9D03FF0E00CE2CD723A

POSSIBLE SECRETS

295F9BAE7428ED9CCC20E7C359A9D41A22FCCD9108E17BF7BA9337A6F8AE9513

5E5CBA992E0A680D885EB903AEA78E4A45A469103D448EDE3B7ACCC54D521E37F84A4BDD5B06B0970CC2D2BBB715F7B82846F9A0C393914C792E6A923E2117AB805276A975A
ADB5261D91673EA9AAFFEECBFA6183DFCB5D3B7332AA19275AFA1F8EC0B60FB6F66CC23AE4870791D5982AAD1AA9485FD8F4A60126FEB2CF05DB8A7F0F09B3397F3937F2E90B
9E5B9C9B6EF642BC48351C46FB171B9BFA9EF17A961CE96C7E7A7CC3D3D03DFAD1078BA21DA425198F07D2481622BCE45969D9C4D6063D72AB7A0F08B2F49A7CC6AF335E0
8C4720E31476B67299E231F8BD90B39AC3AE3BE0C6B6CACEF8289A2E2873D58E51E029CAFBD55E6841489AB66B5B4B9BA6E2F784660896AFF387D92844CCB8B69475496DE19D
A2E58259B090489AC8E62363CDF82CFD8EF2A427ABCD65750B506F56DDE3B988567A88126B914D7828E2B63A6D7ED0747EC59E0E0A23CE7D8A74C1D2C2A7AFB6A29799620F0
0E11C33787F7DED3B30E1A22D09F1FBDA1ABBBFBF25CAE05A13F812E34563F99410E73B

B4C4EE28CEBC6C2C8AC12952CF37F16AC7EFB6A9F69F4B57FFDA2E4F0DE5ADE038CBC2FFF719D2C18DE0284B8BFEF3B52B8CC7A5F5BF0A3C8D2319A5312557E1

8CB91E82A3386D280F5D6F7E50E641DF152F7109ED5456B412B1DA197FB71123ACD3A729901D1A71874700133107EC53

04026EB7A859923FBC82189631F8103FE4AC9CA2970012D5D46024804801841CA44370958493B205E647DA304DB4CEB08CBBDD1BA39494776FB988B47174DCA88C7E2945283A0
1C89720349DC807F4FBF374F4AEADE3BCA95314DD58CEC9F307A54FFC61EFC006D8A2C9D4979C0AC44AEA74FBEBBB9F772AEDCB620B01A7BA7AF1B320430C8591984F601CD4
C143EF1C7A3

b28ef557ba31dfcbdd21ac46e2a91e3c304f44cb87058ada2cb815151e610046

9B9F605F5A858107AB1EC85E6B41C8AA582CA3511EDDFB74F02F3A6598980BB9

04B6B3D4C356C139EB31183D4749D423958C27D2DCAF98B70164C97A2DD98F5CFF6142E0F7C8B204911F9271F0F3ECEFF8C2701C307E8E4C9E183115A1554062CFB

04017232BA853A7E731AF129F22FF4149563A419C26BF50A4C9D6EEFAD612601DB537DECE819B7F70F555A67C427A8CD9BF18AEB9B56E0C11056FAE6A3

0452DCB034293A117E1F4FF11B30F7199D3144CE6DFEAF2E331F296E071FA0DF9982CFEA7D43F2E

2E45EF571F00786F67B0081B9495A3D95462F5DE0AA185EC

020A601907B8C953CA1481EB10512F78744A3205FD

5363ad4cc05c30e0a5261c028812645a122e22ea20816678df02967c1b23bd72

F5CE40D95B5EB899ABBCCFF5911CB8577939804D6527378B8C108C3D2090FF9BE18E2D33E3021ED2EF32D85822423B6304F726AA854BAE07D0396E9A9ADDC40F

POSSIBLE SECRETS

10B7B4D696E676875615175137C8A16FD0DA2211

b0b4417601b59cbc9d8ac8f935cadaec4f5fbb2f23785609ae466748d9b5a536

0400FAC9DFCBAC8313BB2139F1BB755FEF65BC391F8B36F8F8EB7371FD558B01006A08A41903350678E58528BEBF8A0BEFF867A7CA36716F7E01F81052

b869c82b35d70e1b1ff91b28e37a62ecdc34409b

68A5E62CA9CE6C1C299803A6C1530B514E182AD8B0042A59CAD29F43

6C01074756099122221056911C77D77E77A777E7E7E77FCB

BDB6F4FE3E8B1D9E0DA8C0D46F4C318CEFE4AFE3B6B8551F

5667676A654B20754F356EA92017D946567C46675556F19556A04616B567D223A5E05656FB549016A96656A557

C8619ED45A62E6212E1160349E2BFA844439FAFC2A3FD1638F9E

E95E4A5F737059DC60DF5991D45029409E60FC09

3E1AF419A269A5F866A7D3C25C3DF80AE979259373FF2B182F49D4CE7E1BBC8B

127971af8721782ecffa3

5EEEFCA380D02919DC2C6558BB6D8A5D

36DF0AAFD8B8D7597CA10520D04B

7503CFE87A836AE3A61B8816E25450E6CE5E1C93ACF1ABC1778064FDCBEFA921DF1626BE4FD036E93D75E6A50E3A41E98028FE5FC235F5B889A589CB5215F2A4

e9e642599d355f37c97ffd3567120b8e25c9cd43e927b3a9670fbec5d890141922d2c3b3ad2480093799869d1e846aab49fab0ad26d2ce6a22219d470bce7d777d4a21fbe9c270b57f607002f3cef8393694cf45ee3688c11a8c56ab127a3daf

POSSIBLE SECRETS

cc22d6dfb95c6b25e49c0d6364a4e5980c393aa21668d953

06973B15095675534C7CF7E64A21BD54EF5DD3B8A0326AA936ECE454D2C

fca682ce8e12caba26efccf7110e526db078b05edecbcd1eb4a208f3ae1617ae01f35b91a47e6df63413c5e12ed0899bcd132acd50d99151bdc43ee737592e17

340E7BE2A280EB74E2BE61BADA745D97E8F7C300

3EE30B568FBAB0F883CCEBD46D3F3BB8A2A73513F5EB79DA66190EB085FFA9F492F375A97D860EB4

033C258EF3047767E7EDE0F1FDAA79DAEE3841366A132E163ACED4ED2401DF9C6BDCDE98E8E707C07A2239B1B097

044BA30AB5E892B4E1649DD0928643ADCD46F5882E3747DEF36E956E97

659EF8BA043916EEDE8911702B22

25FBC363582DCEC065080CA8287AAFF09788A66DC3A9E

0401A57A6A7B26CA5EF52FCDB816479700B3ADC94ED1FE674C06E695BABA1D

42debb9da5b3d88cc956e08787ec3f3a09bba5f48b889a74aaf53174aa0fbe7e3c5b8fcd7a53bef563b0e98560328960a9517f4014d3325fc7962bf1e049370d76d1314a76137e792f3f0db859d095e4a5b932024f079ecf2ef09c797452b0770e1350782ed57ddf794979dcef23cb96f183061965c4ebc93c9c71c56b925955a75f94cccf1449ac43d586d0beee43251b0b2287349d68de0d144403f13e802f4146d882e057af19b6f6275c6676c8fa0e3ca2713a3257fd1b27d0639f695e347d8d1cf9ac819a26ca9b04cb0eb9b7b035988d15bbac65212a55239cfc7e58fae38d7250ab9991ffbc97134025fe8ce04c4399ad96569be91a546f4978693c7a

E95E4A5F737059DC60DFC7AD95B3D8139515620C

E4E6DB2995065C407D9D39B8D0967B96704BA8E9C90B

POSSIBLE SECRETS

FFFFFFFFFFFFFFFFC90FDAA22168C234C4C6628B80DC1CD129024E088A67CC74020BBEA63B139B22514A08798E3404DDEF9519B3CD3A431B302B0A6DF25F14374FE1356D6D51C245E485B576625E7EC6F44C42E9A637ED6B0BFF5CB6F406B7EDEE386BFB5A899FA5AE9F24117C4B1FE649286651ECE45B3DC2007CB8A163BF0598DA48361C55D39A69163FA8FD24CF5F83655D23DCA3AD961C62F356208552BB9ED529077096966D670C354E4ABC9804F1746C08CA18217C32905E462E36CE3BE39E772C180E86039B2783A2EC07A28FB5C55DF06F4C52C9DE2BCBF6955817183995497CEA956AE515D2261898FA051015728E5A8AAAC42DAD33170D04507A33A85521ABDF1CBA64ECFB850458DBEF0A8AEA71575D060C7DB3970F85A6E1E4C7ABF5AE8CDB0933D71E8C94E04A25619DCCEE3D2261AD2EE6BF12FFA06D98A0864D87602733EC86A64521F2B18177B200CBBE117577A615D6C770988C0BAD946E208E24FA074E5AB3143DB5BFCE0FD108E4B82D120A93AD2CAFFFFFFFFFFFFFFFF

FFFFFFFFFFFFFFFFFADF85458A2BB4A9AAFDC5620273D3CF1D8B9C583CE2D3695A9E13641146433FBCC939DCE249B3EF97D2FE363630C75D8F681B202AEC4617AD3DF1ED5D5FD65612433F51F5F066ED0856365553DED1AF3B557135E7F57C935984F0C70E0E68B77E2A689DAF3EFE8721DF158A136ADE73530ACCA4F483A797ABC0AB182B324FB61D108A94BB2C8E3FBB96ADAB760D7F4681D4F42A3DE394DF4AE56EDE76372BB190B07A7C8EE0A6D709E02FCE1CDF7E2ECC03404CD28342F619172FE9CE98583FF8E4F1232EEF28183C3FE3B1B4C6FAD733BB5FCBC2EC22005C58EF1837D1683B2C6F34A26C1B2EFA886B4238611FCFDCDE355B3B6519035BBC34F4DEF99C023861B46FC9D6E6C9077AD91D2691F7F7EE598CB0FAC186D91CAEFE130985139270B4130C93BC437944F4FD4452E2D74DD364F2E21E71F54BFF5CAE82AB9C9DF69EE86D2BC522363A0DABC521979B0DEADA1DBF9A42D5C4484E0ABCD06BFA53DDEF3C1B20EE3FD59D7C25E41D2B669E1EF16E6F52C3164DF4FB7930E9E4E58857B6AC7D5F42D69F6D187763CF1D5503400487F55BA57E31CC7A7135C886EFB4318AED6A1E012D9E6832A907600A918130C46DC778F971AD0038092999A333CB8B7A1A1DB93D7140003C2A4ECEA9F98D0ACC0A8291CDCEC97DCF8EC9B55A7F88A46B4DB5A851F44182E1C68A007E5E0DD9020BFD64B645036C7A4E677D2C38532A3A23BA4442CAF53EA63BB454329B7624C8917BDD64B1C0FD4CB38E8C334C701C3ACDAD0657FCCFE C719B1F5C3E4E46041F388147FB4CFDB477A52471F7A9A96910B855322EDB6340D8A00EF092350511E30ABEC1FFF9E3A26E7FB29F8C183023C3587E38DA0077D9B4763E4E4B94B2BBC194C6651E77CAF992EEAAC0232A281BF6B3A739C1226116820AE8DB5847A67CBEF9C9091B462D538CD72B03746AE77F5E62292C311562A846505DC82DB854338AE49F5235C95B91178CCF2DD5CACEF403EC9D1810C6272B045B3B71F9DC6B80D63FDD4A8E9ADB1E6962A69526D43161C1A41D570D7938DAD4A40E329CD0E40E65FFFFFFFFFFFFFFFF

12511cfe811d0f4e6bc688b4d

324A6EDDD512F08C49A99AE0D3F961197A76413E7BE81A400CA681E09639B5FE12E59A109F78BF4A373541B3B9A1

0289FDFBE4ABE193DF9559ECF07AC0CE78554E2784EB8C1ED1A57A

9cdbd84c9f1ac2f38d0f80f42ab952e7338bf511

F1FD178C0B3AD58F10126DE8CE42435B3961ADBCABC8CA6DE8FCF353D86E9C00

8CB91E82A3386D280F5D6F7E50E641DF152F7109ED5456B412B1DA197FB71123ACD3A729901D1A71874700133107EC50

4D696E676875615175985BD3ADBADA21B43A97E2

010090512DA9AF72B08349D98A5DD4C7B0532ECA51CE03E2D10F3B7AC579BD87E909AE40A6F131E9CFCE5BD967

POSSIBLE SECRETS

100997906755055304772081815535925224869841082572053457874823515875577147990529272777244152852699298796483356699682842027972896052747173175480590485607134746852141928680912561502802222185647539190902656116367847270145019066794290930185446216399730872221732889830323194097355403213400972588322876850946740663962

8D91E471E0989CDA27DF505A453F2B7635294F2DDF23E3B122ACC99C9E9F1E14

7BC382C63D8C150C3C72080ACE05AFA0C2BEA28E4FB22787139165EFBA91F90F8AA5814A503AD4EB04A8C7DD22CE2826

026108BABB2CEEBCF787058A056CBE0CFE622D7723A289E08A07AE13EF0D10D171DD8D

79885141663410976897627118935756323747307951916507639758300472692338873533959

1f3bdba585295d9a1110d1df1f9430ef8442c5018976ff3437ef91b81dc0b8132c8d5c39c32d0e004a3092b7d327c0e7a4d26d2c7b69b58f9066652911e457779de

30470ad5a005fb14ce2d9dcd87e38bc7d1b1c5facbaecbe95f190aa7a31d23c4dbbcbe06174544401a5b2c020965d8c2bd2171d3668445771f74ba084d2029d83c1c158547f3a9f1a2715be23d51ae4d3e5a1f6a7064f316933a346d3f529252

B4E134D3FB59EB8BAB57274904664D5AF50388BA

0400D9B67D192E0367C803F39E1A7E82CA14A651350AAE617E8F01CE94335607C304AC29E7DEFBD9CA01F596F927224CDECF6C

E95E4A5F737059DC60DFC7AD95B3D8139515620F

13D56FFAEC78681E68F9DEB43B35BEC2FB68542E27897B79

D35E472036BC4FB7E13C785ED201E065F98FCFA6F6F40DEF4F92B9EC7893EC28FCD412B1F1B32E27

24B7B137C8A14D696E6768756151756FD0DA2E5C

023809B2B7CC1B28CC5A87926AAD83FD28789E81E2C9E3BF10

6b17d1f2e12c4247f8bce6e563a440f277037d812deb33a0f4a13945d898c296

POSSIBLE SECRETS

MQVwithSHA512KDFAndSharedInfo

072546B5435234A422E0789675F432C89435DE5242

77d0f8c4dad15eb8c4f2f8d6726cefd96d5bb399

027B680AC8B8596DA5A4AF8A19A0303FCA97FD7645309FA2A581485AF6263E313B79A2F5

FFFFFFFFFFFFFFFFFADF85458A2BB4A9AAFDC5620273D3CF1D8B9C583CE2D3695A9E13641146433FBCC939DCE249B3EF97D2FE363630C75D8F681B202AEC4617AD3DF1ED5D5FD
65612433F51F5F066ED085636553DED1AF3B557135E7F57C935984F0C70E0E68B77E2A689DAF3EFE8721DF158A136ADE73530ACCA4F483A797ABC0AB182B324FB61D108A94BB
2C8E3FBB96ADAB760D7F4681D4F42A3DE394DF4AE56EDE76372BB190B07A7C8EE0A6D709E02FCE1CDF7E2ECC03404CD28342F619172FE9CE98583FF8E4F1232EEF28183C3FE3B
1B4C6FAD733BB5FCBC2EC22005C58EF1837D1683B2C6F34A26C1B2EFA886B423861285C97FFFFFFFFFFFFFFFF

5AC635D8AA3A93E7B3EBBD55769886BC651D06B0CC53B0F63BCE3C3E27D2604B

04BED5AF16EA3F6A4F62938C4631EB5AF7BDBCDBC31667CB477A1A8EC338F94741669C976316DA6321

29C41E568B77C617EFE5902F11DB96FA9613CD8D03DB08DA

1A8F7EDA389B094C2C071E3647A8940F3C123B697578C213BE6DD9E6C8EC7335DCB228FD1EDF4A39152CBAAF8C0398828041055F94CEEE7E21340780FE41BD

A9FB57DBA1EEA9BC3E660A909D838D726E3BF623D52620282013481D1F6E5374

23456789abcdefghijklmnopqrstvwxyz

D7C134AA264366862A18302575D0FB98D116BC4B6DDEBCA3A5A7939F

9a04f079-9840-4286-ab92-e65be0885f95

103FAEC74D696E676875615175777FC5B191EF30

DB7C2ABF62E35E7628DFAC6561C5

POSSIBLE SECRETS

0228F9D04E900069C8DC47A08534FE76D2B900B7D7EF31F5709F200C4CA205

1C97BEFC54BD7A8B65ACF89F81D4D4ADC565FA45

6EE3CEEB230811759F20518A0930F1A4315A827DAC

b3fb3400dec5c4adceb8655d4c94

004D696E67687561517512D8F03431FCE63B88F4

0403F0EBA16286A2D57EA0991168D4994637E8343E3600D51FBC6C71A0094FA2CDD545B11C5C0C797324F1

0051953EB9618E1C9A1F929A21A0B68540EEA2DA725B99B315F3B8B489918EF109E156193951EC7E937B1652C0BD3BB1BF073573DF883D2C34F1EF451FD46B503F00

023b1660dd701d0839fd45eec36f9ee7b32e13b315dc02610aa1b636e346df671f790f84c5e09b05674dbb7e45c803dd

469A28EF7C28CCA3DC721D044F4496BCCA7EF4146FBF25C9

040D9029AD2C7E5CF4340823B2A87DC68C9E4CE3174C1E6EFDEE12C07D58AA56F772C0726F24C6B89E4ECDAC24354B9E99CAA3F6D3761402CD

0101BAF95C9723C57B6C21DA2EFF2D5ED588BDD5717E212F9D

70B5E1E14031C1F70BBEFE96BDDE66F451754B4CA5F48DA241F331AA396B8D1839A855C1769B1EA14BA53308B5E2723724E090E02DB9

AADD9DB8DBE9C48B3FD4E6AE33C9FC07CB308DB3B3C9D20ED6639CCA70330870553E5C414CA92619418661197FAC10471DB1D381085DDADDB58796829CA90069

71169be7330b3038edb025f1d0f9

03375D4CE24FDE434489DE8746E71786015009E66E38A926DD

fd7f53811d75122952df4a9c2eece4e7f611b7523cef4400c31e3f80b6512669455d402251fb593d8d58fabfc5f5ba30f6cb9b556cd7813b801d346ff26660b76b9950a5a49f9fe8047b1022c24fbbba9d7feb7c61bf83b57e7c6a8a6150f04fb83f6d3c51ec3023554135a169132f675f3ae2b61d72aeff22203199dd14801c7

POSSIBLE SECRETS

7167EFC92BB2E3CE7C8AAFF34E12A9C557003D7C73A6FAF003F99F6CC8482E540F7

4230017757A767FAE42398569B746325D45313AF0766266479B75654E65F

036768ae8e18bb92cfcf005c949aa2c6d94853d0e660bbf854b1c9505fe95a

6127C24C05F38A0AAAF65C0EF02C

01360240043788015936020505

962eddcc369cba8ebb260ee6b6a126d9346e38c5

1A62BA79D98133A16BBAE7ED9A8E03C32E0824D57AEF72F88986874E5AAE49C27BED49A2A95058068426C2171E99FD3B43C5947C857D

26DC5C6CE94A4B44F330B5D9BBD77CBF958416295CF7E1CE6BCCDC18FF8C07B6

6db14acc9e21c820ff28b1d5ef5de2b0

07A526C63D3E25A256A007699F5447E32AE456B50E

68363196144955700784444165611827252895102170888761442055095051287550314083023

5DDA470ABE6414DE8EC133AE28E9BBD7FCEC0AE0FFF2

7d7374168ffe3471b60a857686a19475d3bfa2ff

91E38443A5E82C0D880923425712B2BB658B9196932E02C78B2582FE742DAA28

8d5155894229d5e689ee01e6018a237e2cae64cd

41ECE55743711A8C3CBF3783CD08C0EE4D4DC440D4641A8F366E550DFDB3BB67

C302F41D932A36CDA7A3462F9E9E916B5BE8F1029AC4ACC1

POSSIBLE SECRETS

04B70E0CBD6BB4BF7F321390B94A03C1D356C21122343280D6115C1D21BD376388B5F723FB4C22DFE6CD4375A05A07476444D5819985007E34

11839296a789a3bc0045c8a5fb42c7d1bd998f54449579b446817afbd17273e662c97ee72995ef42640c550b9013fad0761353c7086a272c24088be94769fd16650

f2331836f27deacc936e75b3f1a360bd

04188DA80EB03090F67CBF20EB43A18800F4FF0AFD82FF101207192B95FFC8DA78631011ED6B24CDD573F977A11E794811

04640ECE5C12788717B9C1BA06CBC2A6FEBA85842458C56DDE9DB1758D39C0313D82BA51735CDB3EA499AA77A7D6943A64F7A3F25FE26F06B51BAA2696FA9035DA5B534BD595F5AF0FA2C892376C84ACE1BB4E3019B71634C01131159CAE03CEE9D9932184BEEF216BD71DF2DADF86A627306ECFF96DBB8BACE198B61E00F8B332

0101D556572AABAC800101D556572AABAC8001022D5C91DD173F8FB561DA6899164443051D

7D5A0975FC2C3057EEF67530417AFFE7FB8055C126DC5C6CE94A4B44F330B5D9

883423532389192164791648750360308885314476597252960362792450860609699839

5ac635d8aa3a93e7b3ebbd55769886bc651d06b0cc53b0f63bce3c3e27d2604b

142011741597563481196368286022318089743276138395243738762872573441927459393512718973631166078467600360848946623567625795282774719212241929071046134208380636394084512691828894000571524625445295769349356752728956831541775441763139384457191755096847107846595662547942312293338483924514339614727760681880609734239

1CEF494720115657E18F938D7A7942394FF9425C1458C57861F9EEA6ADBE3BE10

28E9FA9E9D9F5E344D5A9E4BCF6509A7F39789F515AB8F92DDBCBD414D940E93

040369979697AB43897789566789567F787A7876A65400435EDB42EFAFB2989D51FEFCE3C80988F41FF883

3d84f26c12238d7b4f3d516613c1759033b1a5800175d0b1

1E589A8595423412134FAA2DBDEC95C8D8675E58

POSSIBLE SECRETS

040303001D34B856296C16C0D40D3CD7750A93D1D2955FA80AA5F40FC8DB7B2ABDBDE53950F4C0D293CDD711A35B67FB1499AE60038614F1394ABFA3B4C850D927E1E7769C8EEC2D19037BF27342DA639B6DCCFFFE73D69D78C6C27A6009CBBCA1980F8533921E8A684423E43BAB08A576291AF8F461BB2A8B3531D2F0485C19B16E2F1516E23DD3C1A4827AF1B8AC15B

985BD3ADBAD4D696E676875615175A21B43A97E3

A9FB57DBA1EEA9BC3E660A909D838D718C397AA3B561A6F7901E0E82974856A7

0202F9F87B7C574D0BDECF8A22E6524775F98CDEBDCB

4E13CA542744D696E67687561517552F279A8C84

edef8ba9-79d6-4ace-a3c8-27dcd51d21ed

517cc1b727220a94fe13abe8fa9a6ee0

2866537B676752636A68F56554E12640276B649EF7526267

fe0e87005b4e83761908c5131d552a850b3f58b749c37cf5b84d6768

B4050A850C04B3ABF54132565044B0B7D7BFD8BA270B39432355FFB4

c103703e120ae8cc73c9248622f3cd1e

FC1217D4320A90452C760A58EDCD30C8DD069B3C34453837A34ED50CB54917E1C2112D84D164F444F8F74786046A

03188da80eb03090f67cbf20eb43a18800f4ff0afd82ff1012

4099B5A457F9D69F79213D094C4BCD4D4262210B

0307AF69989546103D79329FCC3D74880F33BBE803CB

E0D2EE25095206F5E2A4F9ED229F1F256E79A0E2B455970D8D0D865BD94778C576D62F0AB7519CCD2A1A906AE30D

POSSIBLE SECRETS

c97445f45cdef9f0d3e05e1e585fc297235b82b5be8ff3efca67c59852018192

0066647EDE6C332C7F8C0923BB58213B333B20E9CE4281FE115F7D8F90AD

040060F05F658F49C1AD3AB1890F7184210EFD0987E307C84C27ACCFB8F9F67CC2C460189EB5AAAA62EE222EB1B35540CFE902374601E369050B7C4E42ACBA1DACBF04299C3460782F918EA427E6325165E9EA10E3DA5F6C42E9C55215AA9CA27A5863EC48D8E0286B

0405F939258DB7DD90E1934F8C70B0DFEC2EED25B8557EAC9C80E2E198F8CDBECD86B1205303676854FE24141CB98FE6D4B20D02B4516FF702350EDDB0826779C813F0DF45BE8112F4

03E5A88919D7CAFCBF415F07C2176573B2

0095E9A9EC9B297BD4BF36E059184F

e8b4011604095303ca3b8099982be09fcb9ae616

BD71344799D5C7FCDC45B59FA3B9AB8F6A948BC5

02120FC05D3C67A99DE161D2F4092622FECA701BE4F50F4758714E8A87BBF2A658EF8C21E7C5EFE965361F6C2999C0C247B0DBD70CE6B7

002757A1114D696E6768756151755316C05E0BD4

10E723AB14D696E6768756151756FEBF8FCB49A9

3086d221a7d46bcde86c90e49284eb153dab

c49d360886e704936a6678e1139d26b7819f7e90

60dcd2104c4cbc0be6eeefc2bdd610739ec34e317f9b33046c9e4788

85E25BFE5C86226CDB12016F7553F9D0E693A268

DB7C2ABF62E35E668076BEAD208B

POSSIBLE SECRETS

FFFFFFFFFFFFFFFFC90FDAA22168C234C4C6628B80DC1CD129024E088A67CC74020BBEA63B139B22514A08798E3404DDEF9519B3CD3A431B302B0A6DF25F14374FE1356D6D51C245E485B576625E7EC6F44C42E9A637ED6B0BFF5CB6F406B7EDEE386BFB5A899FA5AE9F24117C4B1FE649286651ECE45B3DC2007CB8A163BF0598DA48361C55D39A69163FA8FD24CF5F83655D23DCA3AD961C62F356208552BB9ED529077096966D670C354E4ABC9804F1746C08CA18217C32905E462E36CE3BE39E772C180E86039B2783A2EC07A28FB5C55DF06F4C52C9DE2BCBF6955817183995497CEA956AE515D2261898FA051015728E5A8AAAC42DAD33170D04507A33A85521ABDF1CBA64ECFB850458DBEF0A8AEA71575D060C7DB3970F85A6E1E4C7ABF5AE8CDB0933D71E8C94E04A25619DCEE3D2261AD2EE6BF12FFA06D98A0864D87602733EC86A64521F2B18177B200CBBE117577A615D6C770988C0BAD946E208E24FA074E5AB3143DB5BFCE0FD108E4B82D120A92108011A723C12A787E6D788719A10BDBA5B2699C327186AF4E23C1A946834B6150BDA2583E9CA2AD44CE8DBBBC2DB04DE8EF92E8EFC141FBCEAA6287C59474E6BC05D99B2964FA090C3A2233BA186515BE7ED1F612970CEE2D7AFB81BDD762170481CD0069127D5B05AA993B4EA988D8FDDC186FFB7DC90A6C08F4DF435C93402849236C3FAB4D27C7026C1D4DCB2602646DEC9751E763DBA37BDF8FF9406AD9E530EE5DB382F413001AEB06A53ED9027D831179727B0865A8918DA3EDBEBECF9B14ED44CE6CBACED4BB1BDB7F1447E6CC254B332051512BD7AF426FB8F401378CD2BF5983CA01C64B92ECF032EA15D1721D03F482D7CE6E74FEF6D55E702F46980C82B5A84031900B1C9E59E7C97FBEC7E8F323A97A7E36CC88BE0F1D45B7FF585AC54BD407B22B4154AAC8F6D7EBF48E1D814CC5ED20F8037E0A79715EEF29BE32806A1D58BB7C5DA76F550AA3D8A1FBFF0EB19CCB1A313D55CDA56C9EC2EF29632387FE8D76E3C0468043E8F663F4860EE12BF2D5B0B7474D6E694F91E6DBE115974A3926F12FEE5E438777CB6A932DF8CD8BEC4D073B931BA3BC832B68D9DD300741FA7BF8AFC47ED2576F6936BA424663AAB639C5AE4F5683423B4742BF1C978238F16CBE39D652DE3FDB8BEFC848AD92222E04A4037C0713EB57A81A23F0C73473FC646CEA306B4BCBC8862F8385DDFA9D4B7FA2C087E879683303ED5BDD3A062B3CF5B3A278A66D2A13F83F44F82DDF310EE074AB6A364597E899A0255DC164F31CC50846851DF9AB48195DED7EA1B1D510BD7EE74D73FAF36BC31ECFA268359046F4EB879F924009438B481C6CD7889A002ED5EE382BC9190DA6FC026E479558E4475677E9AA9E3050E2765694DFC81F56E880B96E7160C980DD98EDD3DFFFFFFFFFFFFFFFF

0108B39E77C4B108BED981ED0E890E117C511CF072

C196BA05AC29E1F9C3C72D56DFFC6154A033F1477AC88EC37F09BE6C5BB95F51C296DD20D1A28A067CCC4D4316A4BD1DCA55ED1066D438C35AEBAABF57E7DAE428782A95ECA1C143DB701FD48533A3C18F0FE23557EA7AE619ECACC7E0B51652A8776D02A425567DED36EABD90CA33A1E8D988F0BBB92D02D1D20290113BB562CE1FC856EEB7CDD92D33EEA6F410859B179E7E789A8F75F645FAE2E136D252BFFAFF89528945C1ABE705A38DBC2D364AADE99BE0D0AAD82E5320121496DC65B3930E38047294FF877831A16D5228418DE8AB275D7D75651CEFED65F78AFC3EA7FE4D79B35F62A0402A1117599ADAC7B269A59F353CF450E6982D3B1702D9CA83

74D59FF07F6B413D0EA14B344B20A2DB049B50C3

e4437ed6010e88286f547fa90abfe4c42212

2580F63CCFE44138870713B1A92369E33E2135D266DBB372386C400B

FFFFFFFFFFFFFFFFAD7F85458A2BB4A9AAFDC5620273D3CF1D8B9C583CE2D3695A9E13641146433FBCC939DCE249B3EF97D2FE363630C75D8F681B202AEC4617AD3DF1ED5D5FD65612433F51F5F066ED085636553DED1AF3B557135E7F57C935984F0C70E0E68B77E2A689DAF3EFE8721DF158A136ADE73530ACCA4F483A797ABC0AB182B324FB61D108A94BB2C8E3FBB96ADAB760D7F4681D4F42A3DE394DF4AE56EDE76372BB190B07A7C8EE0A6D709E02FCE1CDF7E2ECC03404CD28342F619172FE9CE98583FF8E4F1232EEF28183C3FE3B1B4C6FAD733BB5FCBC2EC22005C58EF1837D1683B2C6F34A26C1B2E2FFA886B4238611FCFDCE355B3B6519035BBC34F4DEF99C023861B46FC9D6E6C9077AD91D2691F7F7EE598CB0FAC186D91CAEFE130985139270B4130C93BC437944F4FD4452E2D74DD364F2E21E71F54BFF5CAE82AB9C9DF69EE86D2BC522363A0DABC521979B0DEADA1DBF9A42D5C4484E0ABCD06BFA53DDEF3C1B20EE3FD59D7C25E41D2B669E1EF16E6F52C3164DF4FB7930E9E4E58857B6AC7D5F42D69F6D187763CF1D5503400487F55BA57E31CC7A7135C886EFB4318AED6A1E012D9E6832A907600A918130C46DC778F971AD0038092999A333CB8B7A1A1DB93D7140003C2A4ECEA9F98D0ACC0A8291CDCEC97DCF8EC9B55A7F88A46B4DB5A851F44182E1C68A007E5E655F6AFFFFFFFFFFFFFFFF

POSSIBLE SECRETS

31a92ee2029fd10d901b113e990710f0d21ac6b6

77E2B07370EB0F832A6DD5B62DFC88CD06BB84BE

0021A5C2C8EE9FEB5C4B9A753B7B476B7FD6422EF1F3DD674761FA99D6AC27C8A9A197B272822F6CD57A55AA4F50AE317B13545F

0402FE13C0537BBC11ACAA07D793DE4E6D5E5C94EEE80289070FB05D38FF58321F2E800536D538CCDAA3D9

BB8E5E8FBC115E139FE6A814FE48AAA6F0ADA1AA5DF91985

0163F35A5137C2CE3EA6ED8667190B0BC43ECD69977702709B

F1FD178C0B3AD58F10126DE8CE42435B3961ADBCABC8CA6DE8FCF353D86E9C03

C2173F1513981673AF4892C23035A27CE25E2013BF95AA33B22C656F277E7335

027d29778100c65a1da1783716588dce2b8b4aee8e228f1896

95475cf5d93e596c3fcd1d902add02f427f5f3c7210313bb45fb4d5bb2e5fe1cbd678cd4bbdd84c9836be1f31c0777725aeb6c2fc38b85f48076fa76bcd8146cc89a6fb2f706dd719898c2083dc8d896f84062e2c9c94d137b054a8d8096adb8d51952398eeca852a0af12df83e475aa65d4ec0c38a9560d5661186ff98b9fc9eb60eee8b030376b236bc73be3acdbd74fd61c1d2475fa3077b8f080467881ff7e1ca56fee066d79506ade51edbb5443a563927dbc4ba520086746175c8885925ebc64c6147906773496990cb714ec667304e261faee33b3cbdf008e0c3fa90650d97d3909c9275bf4ac86ffcb3d03e6dfc8ada5934242dd6d3bcca2a406cb0b

10D9B4A3D9047D8B154359ABFB1B7F5485B04CEB868237DDC9DEDA982A679A5A919B626D4E50A8DD731B107A9962381FB5D807BF2618

401028774D7777C7B7666D1366EA432071274F89FF01E718

04B8266A46C55657AC734CE38F018F2192

520883949DFDBC42D3AD198640688A6FE13F41349554B49ACC31DCCD884539816F5EB4AC8FB1F1A6

040356DCD8F2F95031AD652D23951BB366A80648F06D867940A5366D9E265DE9EB240F

POSSIBLE SECRETS

021085E2755381DCCCE3C1557AFA10C2F0C0C2825646C5B34A394CBCFA8BC16B22E7E789E927BE216F02E1FB136A5F

3617de4a96262c6f5d9e98bf9292dc29f8f41dbd289a147ce9da3113b5f0b8c00a60b1ce1d7e819d7a431d7c90ea0e5f

041D1C64F068CF45FFA2A63A81B7C13F6B8847A3E77EF14FE3DB7FCAFE0CBD10E8E826E03436D646AAEF87B2E247D4AF1E8ABE1D7520F9C2A45CB1EB8E95CFD55262B70B29FE
EC5864E19C054FF99129280E4646217791811142820341263C5315

00689918DBEC7E5A0DD6DFC0AA55C7

0236B3DAF8A23206F9C4F299D7B21A9C369137F2C84AE1AA0D

CFA0478A54717B08CE64805B76E5B14249A77A4838469DF7F7DC987EFCCFB11D

49f946663a8deb7054212b8adda248c6

114ca50f7a8e2f3f657c1108d9d44cf8

32010857077C5431123A46B808906756F543423E8D27877578125778AC76

258EAF5-E914-47DA-95CA-C5AB0DC85B11

02A29EF207D0E9B6C55CD260B306C7E007AC491CA1B10C62334A9E8DCD8D20FB7

0481AEE4BDD82ED9645A21322E9C4C6A9385ED9F70B5D916C1B43B62EEF4D0098EFF3B1F78E2D0D48D50D1687B93B97D5F7C6D5047406A5E688B352209BCB9F8227DDE385D
566332ECC0EABFA9CF7822FDF209F70024A57B1AA000C55B881F8111B2DCDE494A5F485E5BCA4BD88A2763AED1CA2B2FA8F0540678CD1E0F3AD80892

d09e8800291cb85396cc6717393284aaa0da64ba

0429A0B6A887A983E9730988A68727A8B2D126C44CC2CC7B2A6555193035DC76310804F12E549BDB011C103089E73510ACB275FC312A5DC6B76553F0CA

64210519E59C80E70FA7E9AB72243049FEB8DEECC146B9B1

FFFFFFFF00000000FFFFFFFFFFFFFFFFBCE6FAADA7179E84F3B9CAC2FC632551

POSSIBLE SECRETS

32879423AB1A0375895786C4BB46E9565FDE0B5344766740AF268ADB32322E5C

AADD9DB8DBE9C48B3FD4E6AE33C9FC07CB308DB3B3C9D20ED6639CCA703308717D4D9B009BC66842AECDA12AE6A380E62881FF2F2D82C68528AA6056583A48F0

00C9517D06D5240D3CFF38C74B20B6CD4D6F9DD4D9

7F519EADA7BDA81BD826DBA647910F8C4B9346ED8CCDC64E4B1ABD11756DCE1D2074AA263B88805CED70355A33B471EE

133531813272720673433859519948319001217942375967847486899482359599369642528734712461590403327731821410328012529253871914788598993103310567744136
196364803064721377826656898686468463277710150809401182608770201615324990468332931294920912776241137878030224355746606283971659376426832674269780
880061631528163475887

04DB4FF10EC057E9AE26B07D0280B7F4341DA5D1B1EAE06C7D9B2F2F6D9C5628A7844163D015BE86344082AA88D95E2F9D

A9FB57DBA1EEA9BC3E660A909D838D726E3BF623D52620282013481D1F6E5377

1053CDE42C14D696E67687561517533BF3F83345

9DEF3CAFB939277AB1F12A8617A47BBDBA51DF499AC4C80BEEEE9614B19CC4D5F4F5F556E27CBDE51C6A94BE4607A291558903BA0D0F84380B655BB9A22E8DCDF028A7CEC6
7F0D08134B1C8B97989149B609E0BE3BAB63D47548381DBC5B1FC764E3F4B53DD9DA1158BFD3E2B9C8CF56EDF019539349627DB2FD53D24B7C48665772E437D6C7F8CE44273
4AF7CCB7AE837C264AE3A9BEB87F8A2FE9B8B5292E5A021FFF5E91479E8CE7A28C2442C6F315180F93499A234DCF76E3FED135F9BB

00C9BB9E8927D4D64C377E2AB2856A5B16E3EFB7F61D4316AE

3FCDA526B6CDF83BA1118DF35B3C31761D3545F32728D003EEB25EFE96

2472E2D0197C49363F1FE7F5B6DB075D52B6947D135D8CA445805D39BC345626089687742B6329E70680231988

FFFFFFFFFFFFFFFFADFF85458A2BB4A9AAFDC5620273D3CF1D8B9C583CE2D3695A9E13641146433FBCC939DCE249B3EF97D2FE363630C75D8F681B202AEC4617AD3DF1ED5D5FD
65612433F51F5F066ED085636553DED1AF3B557135E7F57C935984F0C70E0E68B77E2A689DAF3EFE8721DF158A136ADE73530ACCA4F483A797ABC0AB182B324FB61D108A94BB
2C8E3FBB96ADAB760D7F4681D4F42A3DE394DF4AE56EDE76372BB190B07A7C8EE0A6D709E02FCE1CDF7E2ECC03404CD28342F619172FE9CE98583FF8E4F1232EEF28183C3FE3B
1B4C6FAD733BB5FCBC2EC22005C58EF1837D1683B2C6F34A26C1B2EFA886B4238611FCFDCDE355B3B6519035BBC34F4DEF99C023861B46FC9D6E6C9077AD91D2691F7F7EE59
8CB0FAC186D91CAEFE130985139270B4130C93BC437944F4FD4452E2D74DD364F2E21E71F54BFF5CAE82AB9C9DF69EE86D2BC522363A0DABC521979B0DEADA1DBF9A42D5C44
84E0ABCD06BFA53DDEF3C1B20EE3FD59D7C25E41D2B66C62E37FFFFFFFFFFFFFFFF

POSSIBLE SECRETS

c469684435deb378c4b65ca9591e2a5763059a2e

393C7F7D53666B5054B5E6C6D3DE94F4296C0C599E2E2E241050DF18B6090BDC90186904968BB

7BC86E2102902EC4D5890E8B6B4981ff27E0482750FEFC03

046AB1E344CE25FF3896424E7FFE14762ECB49F8928AC0C76029B4D5800374E9F5143E568CD23F3F4D7C0D4B1E41C8CC0D1C6ABD5F1A46DB4C

02197B07845E9BE2D96ADB0F5F3C7F2CFFBD7A3EB8B6FEC35C7FD67F26DDF6285A644F740A2614

F1FD178C0B3AD58F10126DE8CE42435B53DC67E140D2BF941FFDD459C6D655E1

000E0D4D696E6768756151750CC03A4473D03679

91771529896554605945588149018382750217296858393520724172743325725474374979801

0479BE667EF9DCBBAC55A06295CE870B07029BFCDB2DCE28D959F2815B16F81798483ADA7726A3C4655DA4FBFC0E1108A8FD17B448A68554199C47D08FFB10D4B8

04A3E8EB3CC1CFE7B7732213B23A656149AFA142C47AAFBC2B79A191562E1305F42D996C823439C56D7F7B22E14644417E69BCB6DE39D027001DABE8F35B25C9BE

B99B99B099B323E02709A4D696E6768756151751

0443BD7E9AFB53D8B85289BCC48EE5BFE6F20137D10A087EB6E7871E2A10A599C710AF8D0D39E2061114FDD05545EC1CC8AB4093247F77275E0743FFED117182EAA9C77877AA
AC6AC7D35245D1692E8EE1

5D9306BACD22B7FAEB09D2E049C6E2866C5D1677762A8F2F2DC9A11C7F7BE8340AB2237C7F2A0

10B51CC12849B234C75E6DD2028BF7FF5C1CE0D991A1

00E8BEE4D3E2260744188BE0E9C723

04B199B13B9B34EFC1397E64BAEB05ACC265FF2378ADD6718B7C7C1961F0991B842443772152C9E0AD

POSSIBLE SECRETS

MQVwithSHA384KDFAndSharedInfo

687D1B459DC841457E3E06CF6F5E2517B97C7D614AF138BCBF85DC806C4B289F3E965D2DB1416D217F8B276FAD1AB69C50F78BEE1FA3106EFB8CCBC7C5140116

0238af09d98727705120c921bb5e9e26296a3cdcf2f35757a0eafd87b830e7

D7C134AA264366862A18302575D1D787B09F075797DA89F57EC8C0FF

04015D4860D088DDB3496B0C6064756260441CDE4AF1771D4DB01FFE5B34E59703DC255A868A1180515603AEAB60794E54BB7996A70061B1CFAB6BE5F32BBFA78324ED106A7636B9C5A7BD198D0158AA4F5488D08F38514F1FDF4B4F40D2181B3681C364BA0273C706

E87579C11079F43DD824993C2CEE5ED3

96341f1138933bc2f503fd44

B3312FA7E23EE7E4988E056BE3F82D19181D9C6EFE8141120314088F5013875AC656398D8A2ED19D2A85C8EDD3EC2AEF

7ae96a2b657c07106e64479eac3434e99cf0497512f58995c1396c28719501ee

E8C2505DEDFC86DDC1BD0B2B6667F1DA34B82574761CB0E879BD081CFD0B6265EE3CB090F30D27614CB4574010DA90DD862EF9D4EBEE4761503190785A71C760

EEAF0AB9ADB38DD69C33F80AFA8FC5E86072618775FF3C0B9EA2314C9C256576D674DF7496EA81D3383B4813D692C6E0E0D5D8E250B98BE48E495C1D6089DAD15DC7D7B46154D6B6CE8EF4AD69B15D4982559B297BCF1885C529F566660E57EC68EDBC3C05726CC02FD4CBF4976EAA9AFD5138FE8376435B9FC61D2FC0EB06E3

EE353FCA5428A9300D4ABA754A44C00DFEFC0C9AE4B1A1803075ED967B7BB73F

3FA8124359F96680B83D1C3EB2C070E5C545C9858D03ECFB744BF8D717717EFC

127021248288932417465907042777176443525787653508916535812817507265705031260985098497423188333483401180925999995120988934130659205614996724254121049274349357074920312769561451689224110579311248812610229678534638401693520013288995000362260684222750813532307004517341633685004541062586971416883686778842537820383

04A8C7DD22CE28268B39B55416F0447C2FB77DE107DCD2A62E880EA53EEB62D57CB4390295DBC9943AB78696FA504C11

POSSIBLE SECRETS

16a09e667f3bcc908b2fb1366ea957d3e3adec17512775099da2f590b0667322a

03CE10490F6A708FC26DFE8C3D27C4F94E690134D5BFF988D8D28AAEADE975936C66BAC536B18AE2DC312CA493117DAA469C640CAF3

FFFFFFFFFFFFFADF85458A2BB4A9AAFDC5620273D3CF1D8B9C583CE2D3695A9E13641146433FBCC939DCE249B3EF97D2FE363630C75D8F681B202AEC4617AD3DF1ED5D5FD
65612433F51F5F066ED0856365553DED1AF3B557135E7F57C935984F0C70E0E68B77E2A689DAF3EFE8721DF158A136ADE73530ACCA4F483A797ABC0AB182B324FB61D108A94BB
2C8E3FBB96ADAB760D7F4681D4F42A3DE394DF4AE56EDE76372BB190B07A7C8EE0A6D709E02FCE1CDF7E2ECC03404CD28342F619172FE9CE98583FF8E4F1232EEF28183C3FE3B
1B4C6FAD733BB5FCBC2EC22005C58EF1837D1683B2C6F34A26C1B2E2FFA886B4238611FCFDCDE355B3B6519035BBC34F4DEF99C023861B46FC9D6E6C9077AD91D2691F7F7EE59
8CB0FAC186D91CAEFE130985139270B4130C93BC437944F4FD4452E2D74DD364F2E21E71F54BFF5CAE82AB9C9DF69EE86D2BC522363A0DABC521979B0DEADA1DBF9A42D5C44
84E0ABCD06BFA53DDEF3C1B20EE3FD59D7C25E41D2B669E1EF16E6F52C3164DF4FB7930E9E4E58857B6AC7D5F42D69F6D187763CF1D5503400487F55BA57E31CC7A7135C886E
FB4318AED6A1E012D9E6832A907600A918130C46DC778F971AD0038092999A333CB8B7A1A1DB93D7140003C2A4ECEA9F98D0ACCOA8291CDCEC97DCF8EC9B55A7F88A46B4DB
5A851F44182E1C68A007E5E0DD9020BFD64B645036C7A4E677D2C38532A3A23BA4442CAF53EA63BB454329B7624C8917BDD64B1C0FD4CB38E8C334C701C3ACDAD0657FCCFE
C719B1F5C3E4E46041F388147FB4CFDB477A52471F7A9A96910B855322EDB6340D8A00EF092350511E30ABEC1FFF9E3A26E7FB29F8C183023C3587E38DA0077D9B4763E4E4B94
B2BBC194C6651E77CAF992EEAAC0232A281BF6B3A739C1226116820AE8DB5847A67CBEF9C9091B462D538CD72B03746AE77F5E62292C311562A846505DC82DB854338AE49F52
35C95B91178CCF2DD5CACF403EC9D1810C6272B045B3B71F9DC6B80D63FDD4A8E9ADB1E6962A69526D43161C1A41D570D7938DAD4A40E329CFF46AAA36AD004CF600C838
1E425A31D951AE64FDB23FCEC9509D43687FEB69EDD1CC5E0B8CC3BDF64B10EF86B63142A3AB8829555B2F747C932665CB2C0F1CC01BD70229388839D2AF05E454504AC78B7
582822846C0BA35C35F5C59160CC046FD8251541FC68C9C86B022BB7099876A460E7451A8A93109703FEE1C217E6C3826E52C51AA691E0E423CFC99E9E31650C1217B624816CD
AD9A95F9D5B8019488D9C0A0A1FE3075A577E23183F81D4A3F2FA4571EFC8CE0BA8A4FE8B6855DFE72B0A66EDED2FBABFBE58A30FAFABE1C5D71A87E2F741EF8C1FE86FEA6BB
FDE530677F0D97D11D49F7A8443D0822E506A9F4614E011E2A94838FF88CD68C8BB7C5C6424CFFFFFFFFFFFFFFFF

64210519e59c80e70fa7e9ab72243049feb8deecc146b9b1

4A6E0856526436F2F88DD07A341E32D04184572BEB710

0370F6E9D04D289C4E89913CE3530BFDE903977D42B146D539BF1BDE4E9C92

FFFFFFFFE000000075A30D1B9038A115

020ffa963cdca8816ccc33b8642bedf905c3d358573d3f27fbbd3b3cb9aaaf

8e722de3125bdbb05580164bfe20b8b432216a62926c57502ceede31c47816edd1e89769124179d0b695106428815065

2E2F85F5DD74CE983A5C4237229DAF8A3F35823BE

POSSIBLE SECRETS

04AA87CA22BE8B05378EB1C71EF320AD746E1D3B628BA79B9859F741E082542A385502F25DBF55296C3A545E3872760AB73617DE4A96262C6F5D9E98BF9292DC29F8F41DBD289A147CE9DA3113B5F0B8C00A60B1CE1D7E819D7A431D7C90EA0E5F

7CBBBCF9441CFAB76E1890E46884EAE321F70C0BCB4981527897504BEC3E36A62BCDFA2304976540F6450085F2DAE145C22553B465763689180EA2571867423E

90EAF4D1AF0708B1B612FF35E0A2997EB9E9D263C9CE659528945C0D

BDD97E555A50A908E43B01C798EA5DAA6788F1EA2794EFCF57166B8C14039601E55827340BE

51DEF1815DB5ED74FCC34C85D709

04009D73616F35F4AB1407D73562C10F00A52830277958EE84D1315ED31886

1A827EF00DD6FC0E234CAF046C6A5D8A85395B236CC4AD2CF32A0CADBDC9DDF620B0EB9906D0957F6C6FEACD615468DF104DE296CD8F

617fab6832576cbbfed50d99f0249c3fee58b94ba0038c7ae84c8c832f2c

07A11B09A76B562144418FF3FF8C2570B8

22123dc2395a05caa7423daecc94760a7d462256bd56916

040081BAF91FDF9833C40F9C181343638399078C6E7EA38C001F73C8134B1B4EF9E150

04925BE9FB01AFC6FB4D3E7D4990010F813408AB106C4F09CB7EE07868CC136FFF3357F624A21BED5263BA3A7A27483EBF6671DBEF7ABB30EBEE084E58A0B077AD42A5A0989D1EE71B1B9BC0455FB0D2C3

AC6BDB41324A9A9BF166DE5E1389582FAF72B6651987EE07FC3192943DB56050A37329CBB4A099ED8193E0757767A13DD52312AB4B03310DCD7F48A9DA04FD50E8083969EDB767B0CF6095179A163AB3661A05FBD5FAAAE82918A9962F0B93B855F97993EC975EEAA80D740ADBF4FF747359D041D5C33EA71D281E446B14773BCA97B43A23FB801676BD207A436C6481F1D2B9078717461A5B9D32E688F87748544523B524B0D57D5EA77A2775D2ECFA032CFBDBF52FB3786160279004E57AE6AF874E7303CE53299CCC041C7BC308D82A5698F3A8D0C38271AE35F8E9DBFBB694B5C803D89F7AE435DE236D525F54759B65E372FCD68EF20FA7111F9E4AFF73

71169be7330b3038edb025f1

POSSIBLE SECRETS

bb85691939b869c1d087f601554b96b80cb4f55b35f433c2

429418261486158041438734477379555023926723459686071430667981129940894712314200270603852166995638487199576572848148989097707594626134376694563648
827303708389347910808359326479767786019153434744009610342313166725786869204821949328786333602033847970926843422476210557602350161326147806527610
28509445403338652341

90066455B5CFC38F9CAA4A48B4281F292C260FEF01FD61037E56258A7795A1C7AD46076982CE6BB956936C6AB4DCFE05E6784586940CA544B9B2140E1EB523F009D20A7E7880
E4E5BFA690F1B9004A27811CD9904AF70420EEFD6EA11EF7DA129F58835FF56B89FAA637BC9AC2EFAAB903402229F491D8D3485261CD068699B6BA58A1DDBBEF6DB51E8FE34E
8A78E542D7BA351C21EA8D8F1D29F5D5D15939487E27F4416B0CA632C59EFD1B1EB66511A5A0FBF615B766C5862D0BD8A3FE7A0E0DA0FB2FE1FCB19E8F9996A8EA0FCCDE538
175238FC8B0EE6F29AF7F642773EBE8CD5402415A01451A840476B2FCB0E388D30D4B376C37FE401C2A2C2F941DAD179C540C1C8CE030D460C4D983BE9AB0B20F69144C1AE1
3F9383EA1C08504FB0BF321503EFE43488310DD8DC77EC5B8349B8BFE97C2C560EA878DE87C11E3D597F1FEA742D73EEC7F37BE43949EF1A0D15C3F3E3FC0A8335617055AC913
28EC22B50FC15B941D3D1624CD88BC25F3E941FDCC6200689581BFEC416B4B2CB73

e2719d58-a985-b3c9-781a-b030af78d30e

047B6AA5D85E572983E6FB32A7CDEBC14027B6916A894D3AEE7106FE805FC34B44

FFFFFFFFFFFFFFFF90FDAA22168C234C4C6628B80DC1CD129024E088A67CC74020BBA63B139B22514A08798E3404DDEF9519B3CD3A431B302B0A6DF25F14374FE1356D6D51C
245E485B576625E7EC6F44C42E9A637ED6B0BFF5CB6F406B7EDEE386BFB5A899FA5AE9F24117C4B1FE649286651ECE65381FFFFFFFFFFFFFFFF

7ffffffffffffffffffffffff80000cfa7e8594377d414c03821bc582063

1AB597A5B4477F59E39539007C7F977D1A567B92B043A49C6B61984C3FE3481AAF454CD41BA1F051626442B3C10

0409487239995A5EE76B55F9C2F098A89CE5AF8724C0A23E0E0FF77500

7830A3318B603B89E2327145AC234CC594CBDD8D3DF91610A83441CAEA9863BC2DED5D5AA8253AA10A2EF1C98B9AC8B57F1117A72BF2C7B9E7C1AC4D77FC94CA

0100FAF51354E0E39E4892DF6E319C72C8161603FA45AA7B998A167B8F1E629521

0713612DCDDCB40AAB946BDA29CA91F73AF958AFD9

4D41A619BCC6EADF0448FA22FAD567A9181D37389CA

POSSIBLE SECRETS

03F7061798EB99E238FD6F1BF95B48FEEB4854252B

0217C05610884B63B9C6C7291678F9D341

6b8cf07d4ca75c88957d9d67059037a4

00FDFB49BFE6C3A89FACADAA7A1E5BBC7CC1C2E5D831478814

9CA8B57A934C54DEEDA9E54A7BBAD95E3B2E91C54D32BE0B9DF96D8D35

030024266E4EB5106D0A964D92C4860E2671DB9B6CC5

f8183668ba5fc5bb06b5981e6d8b795d30b8978d43ca0ec572e37e09939a9773

f7e1a085d69b3ddecbcab5c36b857b97994afbbfa3aea82f9574c0b3d0782675159578ebad4594fe67107108180b449167123e84c281613b7cf09328cc8a6e13c167a8b547c8d28e0a3ae1e2bb3a675916ea37f0bfa213562f1fb627a01243bcc4f1bea8519089a883dfe15ae59f06928b665e807b552564014c3bfecf492a

02F40E7E2221F295DE297117B7F3D62F5C6A97FFCB8CEFF1CD6BA8CE4A9A18AD84FFABBD8EFA59332BE7AD6756A66E294AFD185A78FF12AA520E4DE739BACA0C7FFEFF7F2955727A

FFFFFFFFFFFFFFFFC90FDAA22168C234C4C6628B80DC1CD129024E088A67CC74020BBEA63B139B22514A08798E3404DDEF9519B3CD3A431B302B0A6DF25F14374FE1356D6D51C245E485B576625E7EC6F44C42E9A637ED6B0BFF5CB6F406B7EDEE386BFB5A899FA5AE9F24117C4B1FE649286651ECE45B3DC2007CB8A163BF0598DA48361C55D39A69163FA8FD24CF5F83655D23DCA3AD961C62F356208552BB9ED529077096966D670C354E4ABC9804F1746C08CA237327FFFFFFFFFFFFFFFF

038D16C2866798B600F9F08BB4A8E860F3298CE04A5798

115792089210356248762697446949407573530086143415290314195533631308867097853951

43FC8AD242B0B7A6F3D1627AD5654447556B47BF6AA4A64B0C2AFE42CADAB8F93D92394C79A79755437B56995136

FFFFFFFFFFFFFFFFC90FDAA22168C234C4C6628B80DC1CD129024E088A67CC74020BBEA63B139B22514A08798E3404DDEF9519B3CD3A431B302B0A6DF25F14374FE1356D6D51C245E485B576625E7EC6F44C42E9A63A3620FFFFFFFFFFFFFFFF

POSSIBLE SECRETS

A59A749A11242C58C894E9E5A91804E8FA0AC64B56288F8D47D51B1EDC4D65444FECA0111D78F35FC9FDD4CB1F1B79A3BA9CBEE83A3F811012503C8117F98E5048B089E387AF6949BF8784EBD9EF45876F2E6A5A495BE64B6E770409494B7FEE1DBB1E4B2BC2A53D4F893D418B7159592E4FFDF6969E91D770DAEBD0B5CB14C00AD68EC7DC1E5745EA55C706C4A1C5C88964E34D09DEB753AD418C1AD0F4FDFD049A955E5D78491C0B7A2F1575A008CCD727AB376DB6E695515B05BD412F5B8C2F4C77EE10DA48ABD53F5DD498927EE7B692BBBCDA2FB23A516C5B4533D73980B2A3B60E384ED200AE21B40D273651AD6060C13D97FD69AA13C5611A51B9085

003088250CA6E7C7FE649CE85820F7

662C61C430D84EA4FE66A7733D0B76B7BF93EBC4AF2F49256AE58101FEE92B04

A335926AA319A27A1D00896A6773A4827ACDAC73

aa87ca22be8b05378eb1c71ef320ad746e1d3b628ba79b9859f741e082542a385502f25dbf55296c3a545e3872760ab7

3086d221a7d46bcde86c90e49284eb15

139454871199115825601409655107690713107041707059928031797758001454375765357722984094124368522288239833039114681648076688236921220737322672160740747771700911134550432053804647694904686120113087816240740184800477047157336662926249423571248823968542221753660143391485680840520336859458494803187341288580489525163

07B6882CAAFA84F9554FF8428BD88E246D2782AE2

A7F561E038EB1ED560B3D147DB782013064C19F27ED27C6780AAF77FB8A547CEB5B4FEF422340353

b8adf1378a6eb73409fa6c9c637ba7f5

POSSIBLE SECRETS

FFFFFFFFFFFFFFFFC90FDAA22168C234C4C6628B80DC1CD129024E088A67CC74020BBEA63B139B22514A08798E3404DDEF9519B3CD3A431B302B0A6DF25F14374FE1356D6D51C245E485B576625E7EC6F44C42E9A637ED6B0BFF5CB6F406B7EDEE386BFB5A899FA5AE9F24117C4B1FE649286651ECE45B3DC2007CB8A163BF0598DA48361C55D39A69163FA8FD24CF5F83655D23DCA3AD961C62F356208552BB9ED529077096966D670C354E4ABC9804F1746C08CA18217C32905E462E36CE3BE39E772C180E86039B2783A2EC07A28FB5C55DF06F4C52C9DE2BCBF6955817183995497CEA956AE515D2261898FA051015728E5A8AAAC42DAD33170D04507A33A85521ABDF1CBA64ECFB850458DBEF0A8AEA71575D060C7DB3970F85A6E1E4C7ABF5AE8CDB0933D71E8C94E04A25619DCEE3D2261AD2EE6BF12FFA06D98A0864D87602733EC86A64521F2B18177B200CBBE117577A615D6C770988C0BAD946E208E24FA074E5AB3143DB5BFCE0FD108E4B82D120A92108011A723C12A787E6D788719A10BDBA5B2699C327186AF4E23C1A946834B6150BDA2583E9CA2AD44CE8DBBBC2DB04DE8EF92E8EFC141FBECOA6287C59474E6BC05D99B2964FA090C3A2233BA186515BE7ED1F612970CEE2D7AFB81BDD762170481CD0069127D5B05AA993B4EA988D8FDDC186FFB7DC90A6C08F4DF435C93402849236C3FAB4D27C7026C1D4DCB2602646DEC9751E763DBA37BDF8FF9406AD9E530EE5DB382F413001AEB06A53ED9027D831179727B0865A8918DA3EDBEBCF9B14ED44CE6CBACED4BB1BDB7F1447E6CC254B332051512BD7AF426FB8F401378CD2BF5983CA01C64B92ECF032EA15D1721D03F482D7CE6E74FEF6D55E702F46980C82B5A84031900B1C9E59E7C97FBEC7E8F323A97A7E36CC88BE0F1D45B7FF585AC54BD407B22B4154AAC8F6D7EBF48E1D814CC5ED20F8037E0A79715EEF29BE32806A1D58BB7C5DA76F550AA3D8A1FBFF0EB19CCB1A313D55CDA56C9EC2EF29632387FE8D76E3C0468043E8F663F4860EE12BF2D5B0B7474D6E694F91E6DCC4024FFFFFFFFFFFFFFF

790408F2EEDAF392B012EDEFB3392F30F4327C0CA3F31FC383C422AA8C16

C49D360886E704936A6678E1139D26B7819F7E90

c6858e06b70404e9cd9e3ecb662395b4429c648139053fb521f828af606b4d3dbaa14b5e77efe75928fe1dc127a2ffa8de3348b3c1856a429bf97e7e31c2e5bd66

FFFFFFFFFFFFFFFFC90FDAA22168C234C4C6628B80DC1CD129024E088A67CC74020BBEA63B139B22514A08798E3404DDEF9519B3CD3A431B302B0A6DF25F14374FE1356D6D51C245E485B576625E7EC6F44C42E9A637ED6B0BFF5CB6F406B7EDEE386BFB5A899FA5AE9F24117C4B1FE649286651ECE45B3DC2007CB8A163BF0598DA48361C55D39A69163FA8FD24CF5F83655D23DCA3AD961C62F356208552BB9ED529077096966D670C354E4ABC9804F1746C08CA18217C32905E462E36CE3BE39E772C180E86039B2783A2EC07A28FB5C55DF06F4C52C9DE2BCBF6955817183995497CEA956AE515D2261898FA051015728E5A8AA68FFFFFFFFFFFFFFF

5F49EB26781C0EC6B8909156D98ED435E45FD59918

046B17D1F2E12C4247F8BCE6E563A440F277037D812DEB33A0F4A13945D898C2964FE342E2FE1A7F9B8EE7EB4A7C0F9E162BCE33576B315ECECBB6406837BF51F5

0432C4AE2C1F1981195F9904466A39C9948FE30BBFF2660BE1715A4589334C74C7BC3736A2F4F6779C59BDCCEE36B692153D0A9877CC62A474002DF32E52139F0A0

00F50B028E4D696E676875615175290472783FB1

c39c6c3b3a36d7701b9c71a1f5804ae5d0003f4

044A96B5688EF573284664698968C38BB913CBFC8223A628553168947D59DCC912042351377AC5FB32

POSSIBLE SECRETS

678471b27a9cf44ee91a49c5147db1a9aaf244f05a434d6486931d2d14271b9e35030b71fd73da179069b32e2935630e1c2062354d0da20a6c416e50be794ca4

040503213F78CA44883F1A3B8162F188E553CD265F23C1567A16876913B0C2AC245849283601CCDA380F1C9E318D90F95D07E5426FE87E45C0E8184698E45962364E34116177DD2259

714114B762F2FF4A7912A6D2AC58B9B5C2FCFE76DAEB7129

6A941977BA9F6A435199ACFC51067ED587F519C5ECB541B8E44111DE1D40

MQVwithSHA256KDFAndSharedInfo

a335926aa319a27a1d00896a6773a4827acdac73

043AE9E58C82F63C30282E1FE7BBF43FA72C446AF6F4618129097E2C5667C2223A902AB5CA449D0084B7E5B3DE7CCC01C9

036b17d1f2e12c4247f8bce6e563a440f277037d812deb33a0f4a13945d898c296

0620048D28BCBD03B6249C99182B7C8CD19700C362C46A01

1243ae1b4d71613bc9f780a03690e

C302F41D932A36CDA7A3463093D18DB78FCE476DE1A86297

010092537397ECA4F6145799D62B0A19CE06FE26AD

000102030405060708090A0B0C0D0E0F101112131415161718191A1B1C1D1E1F

0257927098FA932E7C0A96D3FD5B706EF7E5F5C156E16B7E7C86038552E91D

108576C80499DB2FC16EDDF6853BBB278F6B6FB437D9

6b8cf07d4ca75c88957d9d670591

POSSIBLE SECRETS
1854BEBDC31B21B7AEFC80AB0ECD10D5B1B3308E6DBF11C1
03eea2bae7e1497842f2de7769cfe9c989c072ad696f48034a
DB7C2ABF62E35E668076BEAD2088
0401F481BC5F0FF84A74AD6CDF6FDEF4BF6179625372D8C0C5E10025E399F2903712CCF3EA9E3A1AD17FB0B3201B6AF7CE1B05
9ba48cba5ebcb9b6bd33b92830b2a2e0e192f10a
D09E8800291CB85396CC6717393284AAA0DA64BA
6BA06FE51464B2BD26DC57F48819BA9954667022C7D03
0017858FEB7A98975169E171F77B4087DE098AC8A911DF7B01
04C0A0647EAA6A48753B033C56CB0F0900A2F5C4853375FD614B690866ABD5BB88B5F4828C1490002E6773FA2FA299B8F
3045AE6FC8422F64ED579528D38120EAE12196D5

PLAYSTORE INFORMATION

Title: MapSpoto – Local Events

Score: None **Installs:** 100+ **Price:** 0 **Android Version Support:** **Category:** Social **Play Store URL:** com.voivoo.mapspoto

Developer Details: MapSpoto Studio, MapSpoto+Studio, None, <http://www.mapspoto.com>, support@mapspoto.com,

Release Date: Mar 1, 2026 **Privacy Policy:** [Privacy link](#)

Description:

Discover activities and local events around you and connect with your community. MapSpoto is a location-based platform for discovering local events and activities nearby. Users can explore activities happening around them, join events that match their interests, and connect with others through in-app communication. Whether you are looking for social activities, group events, sports activities, or shared interests, MapSpoto helps you discover things to do nearby and meet people in your area. Locations are used only to show

relevant activities and improve discovery. The app does not share users' real-time or exact physical location with others. □ Key features • Discover local events and activities near you • Join and participate in community activities • Connect and communicate with other users • Create and share your own activities and events • Block and report users or content for a safe experience □ MapSpoto is designed to encourage real social interaction through activities, helping people connect with others who share similar interests while providing users with privacy protection, safety tools, and control over their experience.

☰ SCAN LOGS

Timestamp	Event	Error
2026-06-05 05:34:43	Generating Hashes	OK
2026-06-05 05:34:44	Extracting APK	OK
2026-06-05 05:34:44	Unzipping	OK
2026-06-05 05:34:45	Parsing APK with androguard	OK
2026-06-05 05:34:46	Extracting APK features using aapt/aapt2	OK
2026-06-05 05:34:47	Getting Hardcoded Certificates/Keystores	OK
2026-06-05 05:34:52	Parsing AndroidManifest.xml	OK
2026-06-05 05:34:52	Extracting Manifest Data	OK

2026-06-05 05:34:52	Manifest Analysis Started	OK
2026-06-05 05:34:52	Performing Static Analysis on: MapSpoto (com.voivoo.mapspoto)	OK
2026-06-05 05:34:53	Fetching Details from Play Store: com.voivoo.mapspoto	OK
2026-06-05 05:34:54	Checking for Malware Permissions	OK
2026-06-05 05:34:54	Fetching icon path	OK
2026-06-05 05:34:54	Library Binary Analysis Started	OK
2026-06-05 05:34:54	Analyzing lib/arm64-v8a/libreactnative.so	OK
2026-06-05 05:34:54	Analyzing lib/arm64-v8a/libhermestooling.so	OK
2026-06-05 05:34:54	Analyzing lib/arm64-v8a/libavif_android.so	OK
2026-06-05 05:34:54	Analyzing lib/arm64-v8a/libnative-imagetranscoder.so	OK
2026-06-05 05:34:54	Analyzing lib/arm64-v8a/libfbjni.so	OK

2026-06-05 05:34:54	Analyzing lib/arm64-v8a/libc++_shared.so	OK
2026-06-05 05:34:54	Analyzing lib/arm64-v8a/libhermes.so	OK
2026-06-05 05:34:54	Analyzing lib/arm64-v8a/libnative-filters.so	OK
2026-06-05 05:34:54	Analyzing lib/arm64-v8a/libanimation-decoder-gif.so	OK
2026-06-05 05:34:54	Analyzing lib/arm64-v8a/librnscreens.so	OK
2026-06-05 05:34:54	Analyzing lib/arm64-v8a/libsendentry.so	OK
2026-06-05 05:34:54	Analyzing lib/arm64-v8a/libexpo-modules-core.so	OK
2026-06-05 05:34:54	Analyzing lib/arm64-v8a/libgifimage.so	OK
2026-06-05 05:34:54	Analyzing lib/arm64-v8a/libimagepipeline.so	OK
2026-06-05 05:34:54	Analyzing lib/arm64-v8a/libworklets.so	OK
2026-06-05 05:34:54	Analyzing lib/arm64-v8a/libjsi.so	OK

2026-06-05 05:34:54	Analyzing lib/arm64-v8a/libstatic-webp.so	OK
2026-06-05 05:34:54	Analyzing lib/arm64-v8a/libreanimated.so	OK
2026-06-05 05:34:54	Analyzing lib/arm64-v8a/libentry-android.so	OK
2026-06-05 05:34:54	Analyzing lib/x86_64/libreactnative.so	OK
2026-06-05 05:34:54	Analyzing lib/x86_64/libhermestooling.so	OK
2026-06-05 05:34:54	Analyzing lib/x86_64/libavif_android.so	OK
2026-06-05 05:34:54	Analyzing lib/x86_64/libnative-imagetranscoder.so	OK
2026-06-05 05:34:54	Analyzing lib/x86_64/libfbjni.so	OK
2026-06-05 05:34:54	Analyzing lib/x86_64/libc++_shared.so	OK
2026-06-05 05:34:54	Analyzing lib/x86_64/libhermes.so	OK
2026-06-05 05:34:54	Analyzing lib/x86_64/libnative-filters.so	OK

2026-06-05 05:34:55	Analyzing lib/x86_64/libanimation-decoder-gif.so	OK
2026-06-05 05:34:55	Analyzing lib/x86_64/librnscreens.so	OK
2026-06-05 05:34:55	Analyzing lib/x86_64/libentry.so	OK
2026-06-05 05:34:55	Analyzing lib/x86_64/libexpo-modules-core.so	OK
2026-06-05 05:34:55	Analyzing lib/x86_64/libgifimage.so	OK
2026-06-05 05:34:55	Analyzing lib/x86_64/libimagepipeline.so	OK
2026-06-05 05:34:55	Analyzing lib/x86_64/libworklets.so	OK
2026-06-05 05:34:55	Analyzing lib/x86_64/libjsi.so	OK
2026-06-05 05:34:55	Analyzing lib/x86_64/libstatic-webp.so	OK
2026-06-05 05:34:55	Analyzing lib/x86_64/libreanimated.so	OK
2026-06-05 05:34:55	Analyzing lib/x86_64/libentry-android.so	OK

2026-06-05 05:34:55	Analyzing lib/armeabi-v7a/libreactnative.so	OK
2026-06-05 05:34:55	Analyzing lib/armeabi-v7a/libhermestooling.so	OK
2026-06-05 05:34:55	Analyzing lib/armeabi-v7a/libavif_android.so	OK
2026-06-05 05:34:55	Analyzing lib/armeabi-v7a/libnative-imagetranscoder.so	OK
2026-06-05 05:34:55	Analyzing lib/armeabi-v7a/libfbjni.so	OK
2026-06-05 05:34:55	Analyzing lib/armeabi-v7a/libc++_shared.so	OK
2026-06-05 05:34:55	Analyzing lib/armeabi-v7a/libhermes.so	OK
2026-06-05 05:34:55	Analyzing lib/armeabi-v7a/libnative-filters.so	OK
2026-06-05 05:34:55	Analyzing lib/armeabi-v7a/libanimation-decoder-gif.so	OK
2026-06-05 05:34:55	Analyzing lib/armeabi-v7a/librnscreens.so	OK
2026-06-05 05:34:55	Analyzing lib/armeabi-v7a/lib Sentry.so	OK

2026-06-05 05:34:55	Analyzing lib/armeabi-v7a/libexpo-modules-core.so	OK
2026-06-05 05:34:55	Analyzing lib/armeabi-v7a/libgifimage.so	OK
2026-06-05 05:34:55	Analyzing lib/armeabi-v7a/libimagepipeline.so	OK
2026-06-05 05:34:55	Analyzing lib/armeabi-v7a/libworklets.so	OK
2026-06-05 05:34:55	Analyzing lib/armeabi-v7a/libjsi.so	OK
2026-06-05 05:34:55	Analyzing lib/armeabi-v7a/libstatic-webp.so	OK
2026-06-05 05:34:55	Analyzing lib/armeabi-v7a/libreanimated.so	OK
2026-06-05 05:34:55	Analyzing lib/armeabi-v7a/libentry-android.so	OK
2026-06-05 05:34:55	Analyzing lib/x86/libreactnative.so	OK
2026-06-05 05:34:56	Analyzing lib/x86/libhermestooling.so	OK
2026-06-05 05:34:56	Analyzing lib/x86/libavif_android.so	OK

2026-06-05 05:34:56	Analyzing lib/x86/libnative-imagetranscoder.so	OK
2026-06-05 05:34:56	Analyzing lib/x86/libfbjni.so	OK
2026-06-05 05:34:56	Analyzing lib/x86/libc++_shared.so	OK
2026-06-05 05:34:56	Analyzing lib/x86/libhermes.so	OK
2026-06-05 05:34:56	Analyzing lib/x86/libnative-filters.so	OK
2026-06-05 05:34:56	Analyzing lib/x86/libanimation-decoder-gif.so	OK
2026-06-05 05:34:56	Analyzing lib/x86/librnscreens.so	OK
2026-06-05 05:34:56	Analyzing lib/x86/libentry.so	OK
2026-06-05 05:34:56	Analyzing lib/x86/libexpo-modules-core.so	OK
2026-06-05 05:34:56	Analyzing lib/x86/libgifimage.so	OK
2026-06-05 05:34:56	Analyzing lib/x86/libimagepipeline.so	OK

2026-06-05 05:34:56	Analyzing lib/x86/libworklets.so	OK
2026-06-05 05:34:56	Analyzing lib/x86/libjsi.so	OK
2026-06-05 05:34:56	Analyzing lib/x86/libstatic-webp.so	OK
2026-06-05 05:34:56	Analyzing lib/x86/libreanimated.so	OK
2026-06-05 05:34:56	Analyzing lib/x86/lib Sentry-android.so	OK
2026-06-05 05:34:56	Analyzing apktool_out/lib/arm64-v8a/libreactnative.so	OK
2026-06-05 05:34:56	Analyzing apktool_out/lib/arm64-v8a/libhermestooling.so	OK
2026-06-05 05:34:56	Analyzing apktool_out/lib/arm64-v8a/libavif_android.so	OK
2026-06-05 05:34:56	Analyzing apktool_out/lib/arm64-v8a/libnative-image-transcoder.so	OK
2026-06-05 05:34:56	Analyzing apktool_out/lib/arm64-v8a/libfbjni.so	OK
2026-06-05 05:34:56	Analyzing apktool_out/lib/arm64-v8a/libc++_shared.so	OK

2026-06-05 05:34:56	Analyzing apktool_out/lib/arm64-v8a/libhermes.so	OK
2026-06-05 05:34:56	Analyzing apktool_out/lib/arm64-v8a/libnative-filters.so	OK
2026-06-05 05:34:56	Analyzing apktool_out/lib/arm64-v8a/libanimation-decoder-gif.so	OK
2026-06-05 05:34:56	Analyzing apktool_out/lib/arm64-v8a/librnscreens.so	OK
2026-06-05 05:34:56	Analyzing apktool_out/lib/arm64-v8a/lib Sentry.so	OK
2026-06-05 05:34:56	Analyzing apktool_out/lib/arm64-v8a/libexpo-modules-core.so	OK
2026-06-05 05:34:57	Analyzing apktool_out/lib/arm64-v8a/libgifimage.so	OK
2026-06-05 05:34:57	Analyzing apktool_out/lib/arm64-v8a/libimagepipeline.so	OK
2026-06-05 05:34:57	Analyzing apktool_out/lib/arm64-v8a/libworklets.so	OK
2026-06-05 05:34:57	Analyzing apktool_out/lib/arm64-v8a/libjsi.so	OK
2026-06-05 05:34:57	Analyzing apktool_out/lib/arm64-v8a/libstatic-webp.so	OK

2026-06-05 05:34:57	Analyzing apktool_out/lib/arm64-v8a/libreanimated.so	OK
2026-06-05 05:34:57	Analyzing apktool_out/lib/arm64-v8a/libentry-android.so	OK
2026-06-05 05:34:57	Analyzing apktool_out/lib/x86_64/libreactnative.so	OK
2026-06-05 05:34:57	Analyzing apktool_out/lib/x86_64/libhermestooling.so	OK
2026-06-05 05:34:57	Analyzing apktool_out/lib/x86_64/libavif_android.so	OK
2026-06-05 05:34:57	Analyzing apktool_out/lib/x86_64/libnative-imagetranscoder.so	OK
2026-06-05 05:34:57	Analyzing apktool_out/lib/x86_64/libfbjni.so	OK
2026-06-05 05:34:57	Analyzing apktool_out/lib/x86_64/libc++_shared.so	OK
2026-06-05 05:34:57	Analyzing apktool_out/lib/x86_64/libhermes.so	OK
2026-06-05 05:34:57	Analyzing apktool_out/lib/x86_64/libnative-filters.so	OK
2026-06-05 05:34:57	Analyzing apktool_out/lib/x86_64/libanimation-decoder-gif.so	OK

2026-06-05 05:34:57	Analyzing apktool_out/lib/x86_64/librnscreens.so	OK
2026-06-05 05:34:57	Analyzing apktool_out/lib/x86_64/libentry.so	OK
2026-06-05 05:34:57	Analyzing apktool_out/lib/x86_64/libexpo-modules-core.so	OK
2026-06-05 05:34:57	Analyzing apktool_out/lib/x86_64/libgifimage.so	OK
2026-06-05 05:34:57	Analyzing apktool_out/lib/x86_64/libimagepipeline.so	OK
2026-06-05 05:34:57	Analyzing apktool_out/lib/x86_64/libworklets.so	OK
2026-06-05 05:34:57	Analyzing apktool_out/lib/x86_64/libjsi.so	OK
2026-06-05 05:34:57	Analyzing apktool_out/lib/x86_64/libstatic-webp.so	OK
2026-06-05 05:34:57	Analyzing apktool_out/lib/x86_64/libreanimated.so	OK
2026-06-05 05:34:57	Analyzing apktool_out/lib/x86_64/libentry-android.so	OK
2026-06-05 05:34:57	Analyzing apktool_out/lib/armeabi-v7a/libreactnative.so	OK

2026-06-05 05:34:57	Analyzing apktool_out/lib/armeabi-v7a/libhermestooling.so	OK
2026-06-05 05:34:57	Analyzing apktool_out/lib/armeabi-v7a/libavif_android.so	OK
2026-06-05 05:34:57	Analyzing apktool_out/lib/armeabi-v7a/libnative-image-transcoder.so	OK
2026-06-05 05:34:58	Analyzing apktool_out/lib/armeabi-v7a/libfbjni.so	OK
2026-06-05 05:34:58	Analyzing apktool_out/lib/armeabi-v7a/libc++_shared.so	OK
2026-06-05 05:34:58	Analyzing apktool_out/lib/armeabi-v7a/libhermes.so	OK
2026-06-05 05:34:58	Analyzing apktool_out/lib/armeabi-v7a/libnative-filter.so	OK
2026-06-05 05:34:58	Analyzing apktool_out/lib/armeabi-v7a/libanimation-decoder-gif.so	OK
2026-06-05 05:34:58	Analyzing apktool_out/lib/armeabi-v7a/librnscreens.so	OK
2026-06-05 05:34:58	Analyzing apktool_out/lib/armeabi-v7a/libentry.so	OK
2026-06-05 05:34:58	Analyzing apktool_out/lib/armeabi-v7a/libexpo-modules-core.so	OK

2026-06-05 05:34:58	Analyzing apktool_out/lib/armeabi-v7a/libgifimage.so	OK
2026-06-05 05:34:58	Analyzing apktool_out/lib/armeabi-v7a/libimagepipeline.so	OK
2026-06-05 05:34:58	Analyzing apktool_out/lib/armeabi-v7a/libworklets.so	OK
2026-06-05 05:34:58	Analyzing apktool_out/lib/armeabi-v7a/libjsi.so	OK
2026-06-05 05:34:58	Analyzing apktool_out/lib/armeabi-v7a/libstatic-webp.so	OK
2026-06-05 05:34:58	Analyzing apktool_out/lib/armeabi-v7a/libreanimated.so	OK
2026-06-05 05:34:58	Analyzing apktool_out/lib/armeabi-v7a/libentry-android.so	OK
2026-06-05 05:34:58	Analyzing apktool_out/lib/x86/libreactnative.so	OK
2026-06-05 05:34:58	Analyzing apktool_out/lib/x86/libhermestooling.so	OK
2026-06-05 05:34:58	Analyzing apktool_out/lib/x86/libavif_android.so	OK
2026-06-05 05:34:58	Analyzing apktool_out/lib/x86/libnative-image-transcoder.so	OK

2026-06-05 05:34:58	Analyzing apktool_out/lib/x86/libfbjni.so	OK
2026-06-05 05:34:58	Analyzing apktool_out/lib/x86/libc++_shared.so	OK
2026-06-05 05:34:58	Analyzing apktool_out/lib/x86/libhermes.so	OK
2026-06-05 05:34:58	Analyzing apktool_out/lib/x86/libnative-filters.so	OK
2026-06-05 05:34:58	Analyzing apktool_out/lib/x86/libanimation-decoder-gif.so	OK
2026-06-05 05:34:58	Analyzing apktool_out/lib/x86/librnscreens.so	OK
2026-06-05 05:34:58	Analyzing apktool_out/lib/x86/libentry.so	OK
2026-06-05 05:34:59	Analyzing apktool_out/lib/x86/libexpo-modules-core.so	OK
2026-06-05 05:34:59	Analyzing apktool_out/lib/x86/libgifimage.so	OK
2026-06-05 05:34:59	Analyzing apktool_out/lib/x86/libimagepipeline.so	OK
2026-06-05 05:34:59	Analyzing apktool_out/lib/x86/libworklets.so	OK

2026-06-05 05:34:59	Analyzing apktool_out/lib/x86/libjsi.so	OK
2026-06-05 05:34:59	Analyzing apktool_out/lib/x86/libstatic-webp.so	OK
2026-06-05 05:34:59	Analyzing apktool_out/lib/x86/libreanimated.so	OK
2026-06-05 05:34:59	Analyzing apktool_out/lib/x86/libentry-android.so	OK
2026-06-05 05:34:59	Reading Code Signing Certificate	OK
2026-06-05 05:35:00	Running APKiD 3.0.0	OK
2026-06-05 05:35:06	Detecting Trackers	OK
2026-06-05 05:35:15	Decompiling APK to Java with JADX	OK
2026-06-05 05:36:25	Converting DEX to Smali	OK
2026-06-05 05:36:25	Code Analysis Started on - java_source	OK
2026-06-05 05:36:51	Android SBOM Analysis Completed	OK

2026-06-05 05:37:00	Android SAST Completed	OK
2026-06-05 05:37:00	Android API Analysis Started	OK
2026-06-05 05:37:11	Android API Analysis Completed	OK
2026-06-05 05:37:11	Android Permission Mapping Started	OK
2026-06-05 05:37:21	Android Permission Mapping Completed	OK
2026-06-05 05:37:23	Android Behaviour Analysis Started	OK
2026-06-05 05:37:33	Android Behaviour Analysis Completed	OK
2026-06-05 05:37:33	Extracting Emails and URLs from Source Code	OK
2026-06-05 05:37:41	Email and URL Extraction Completed	OK
2026-06-05 05:37:41	Extracting String data from APK	OK
2026-06-05 05:37:41	Extracting String data from SO	OK

2026-06-05 05:37:44	Extracting String data from Code	OK
2026-06-05 05:37:44	Extracting String values and entropies from Code	OK
2026-06-05 05:37:58	Performing Malware check on extracted domains	OK
2026-06-05 05:38:01	Saving to Database	OK

Report Generated by - MobSF v4.5.0

Mobile Security Framework (MobSF) is an automated, all-in-one mobile application (Android/iOS/Windows) pen-testing, malware analysis and security assessment framework capable of performing static and dynamic analysis.

© 2026 Mobile Security Framework - MobSF | [Ajin Abraham](#) | [OpenSecurity](#).